SATCO NUVO

Project Name

ocation Prepared By



Notes

w1 02-12-2025 00:05:4

Title 20 / 24 Status

RoHS Compliant

FCC Compliant

General	
Status	Active
Watts	5.5W
Incandescent Equivalent	60W
Volts	120V
Shape	CA10
Base	Medium
ANSI Base	E26
Finish	Frost
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	90
Lumens	500L
Beam Spread	300
Dimmable	Yes-Dimmable
Dimming Note	120V only
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Franklad	
IOT Enabled	No
Electrical	NO
Electrical	NO 60Hz
Electrical Operating Frequency Power Factor	60Hz
Electrical Operating Frequency	60Hz 0.75
Electrical Operating Frequency Power Factor Operating Position	60Hz 0.75 Universal
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical	60Hz 0.75 Universal -20C (-4F) to +45C (+113F)
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical	60Hz 0.75 Universal -20C (-4F) to +45C (+113F)
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38 0.07
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38
Power Factor Operating Position Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38 0.07
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38 0.07 Yes 3 Year Limited
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38 0.07 Yes 3 Year Limited
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38 0.07 Yes 3 Year Limited CETLus - Listed Wet
Electrical Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	60Hz 0.75 Universal -20C (-4F) to +45C (+113F) 4.33 1.38 0.07 Yes 3 Year Limited

Lawful for sale

Yes

Yes