

Project Name

Location

Prepared By



SATCO S23114

130W/LED/HID-HB/4K/120-277V

Notes

(www) 05-13-2023 23:26:34

General

| | |
|-------------------------|---|
| Status | Discontinued |
| Substitute | S33114 |
| Watts | 130W |
| Incandescent Equivalent | 250W |
| HID Equivalent | 400W |
| Volts | 120V-277V |
| Shape | HB77 |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | Translucent White |
| CCT (Kelvin) | 4000K |
| Temperature | Cool White |
| CRI | 80+ |
| Lumens | 16300L |
| Beam Spread | 115 |
| Dimmable | Yes-Dimmable |
| Hours Rated | 35000 |
| Product Category | Hi-Bay |
| Technology | LED |
| Min Compartment Size | Length: 16.5 in. Width: 16.5 in. Height: 13 in. |
| Ballasting Requirements | Ballast Bypass |

Electrical

| | |
|-----------------------|---|
| Operating Frequency | 50-60Hz |
| Candlepower | 5000 |
| Dimming Type | Step Dimming |
| Dimming Note | Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch |
| Power Factor | 0.99/0.95 |
| Operating Position | Universal |
| Surge Protection | Built-in surge protection - 6KV |
| Operating Temperature | -40C (-40F) to +60C (+140F) |

Physical

| | |
|---------------|---------|
| MOL | 12.4 |
| MOD | 9.65 |
| Lens Material | Plastic |
| Housing Color | White |
| Weight (lb.) | 2.98 |

Additional Information

| | |
|----------------------------|--|
| Rated For Enclosed Fixture | Yes |
| Specification Note | Fixture has a built-in dimming control feature |
| Installation Notes | Not for use in vapor tight fixtures. |
| Warranty | 5-Years |

Compliance

| | |
|----------------------|---------------------------------------|
| Safety Listing | cULus - Classified; cULus - Certified |
| Location Rating | Damp |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |