

Project Name

Location

Prepared By



## SATCO S23150

63W/LED/CCT/100-277V/EX39

### Notes

(revised) 09-07-2023 001-03-13

### General

Status	Active
Watts	63W/54W/45W
Incandescent Equivalent	150W-250W
HID Equivalent	250W/200W/175W
Volts	120V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80+
Lumens	8820L/7560L/6300L
Beam Spread	300
Hours Rated	50000
Product Category	Corncob
Technology	LED
Min Compartment Size	Length: 7.88 in. Width: 7.88 in.
Ballasting Requirements	Ballast Bypass

### Electrical

Operating Frequency	50/60Hz
Power Factor	>0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
THD	14.10%
Operating Temperature	-40C (-40F) to +60C (+140F)

### Physical

MOL	10.28
MOD	3.35
Lens Material	Plastic
Housing Color	Dark Gray
Weight (lb.)	1.8

### Additional Information

Additional Info	Power selectable
Rated For Enclosed Fixture	Yes
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Years

### Compliance

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Damp
DLC Approved	Yes
DLC ID	S-ZHMICR
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp