

Project Name

Prepared By



Notes

6W/LED/CFL/835/GX23/BP/G2

General	
Status	Active
Watts	6W
Fluorescent Equivalent	13W
Volts	120V-277V
Ballast Type	Туре В
Shape	PL
Base	GX23
ANSI Base	GX23
Finish	Frost
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	600L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL 2-Pin
Operating Position	Universal
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	-25C (-13F) to +45C (+113F)
Physical	
MOL	7.09

Operating Temperature	-25C (-13F) to +45C (+113F)
Physical	
MOL	7.09
MOD	1.28
Housing Color	White
Weight (lb.)	0.1

Additional Information	
Rated For Enclosed Fixture	Yes
Warranty	5 Years

Compliance	
Safety Listing	cULus - Certified; cULus - Classified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp