SATCO' NUVO

Project Name

ocation

```
Prepared By
```



Notes

| Conoral | |
|----------------------------|--|
| General | |
| Status | Discontinued |
| Substitute | S28938R1 |
| Watts | 110W |
| Incandescent Equivalent | 750W |
| HID Equivalent | 400W |
| Volts | 120V-277V |
| Shape | Corncob |
| Base | Mogul Extended |
| ANSI Base | EX39 |
| Finish | White |
| CCT (Kelvin) | 3000K |
| Temperature | Warm White |
| CRI Lumens | 80+ 14300L |
| Beam Spread | 143002 |
| Hours Rated | 50000 |
| Product Category | Shoebox |
| Technology | LED |
| Min Compartment Size | Length: 11 in. Width: 11.6 in. Height: 11 in. |
| Ballasting Requirements | Ballast Bypass |
| | |
| Electrical | |
| Operating Frequency | 50/60Hz |
| Power Factor | 0.9 |
| Operating Position | Universal |
| Surge Protection | Built-in surge protection - 4KV |
| THD | 18.10% |
| Operating Temperature | -30C (-22F) to +45C (+113F) |
| Physical | |
| MOL | 11.13 |
| MOD | 4.38 |
| Lens Finish | White |
| Lens Material | Plastic (PS) |
| Housing Color | White |
| Weight (lb.) | 3.67 |
| Additional Information | |
| | |
| Rated For Enclosed Fixture | Yes |
| IP Rating | IP64 |
| Specification Note | This is not to be used with a ballast |
| Installation Notes | Not for use in vapor tight fixtures. |
| Warranty | 5-Years |
| Compliance | |
| Safety Listing | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | PLE2XRXMGJUC |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| Colorado Status | Lawful for sale |
| Hawaii Status | Lawful for sale |
| Nevada Status | Lawful for sale |
| Vermont Status | Lawful for sale |
| Washington Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| SDS Sheet | LED_Lamp |
| | _ · · · · · |

