SATCO NUVO

Project Name

Location

Prepared By



Notes

[www] 01-15-2024 02:40:

General	
Status	Discontinued
Substitute	S49392
Watts	36W
Incandescent Equivalent	200W
Fluorescent Equivalent	55W
HID Equivalent	150W
Volts	100V-277V
Shape	Corncob
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	4800L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 17.3 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 90-305V
Working Voltage Operating Frequency	AC 90-305V 50/60Hz
Operating Frequency	50/60Hz
Operating Frequency Power Factor	50/60Hz >.9
Operating Frequency Power Factor Operating Position	50/60Hz >.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature	50/60Hz >.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 5 Year Limited - Hi-Pro
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 5 Year Limited - Hi-Pro
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Warranty Compliance Safety Listing Location Rating	50/60Hz >.9 Universal -20C (-4F) to +40C (+104F) 9.16 3.66 Clear White 1.68 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; For outdoor & indoor use; Emits no UV light / Contains no Mercury (Hg) Yes IP65 5 Year Limited - Hi-Pro CULus - Listed Wet

CA T20 / T24 Rationale	Exempt - >2600 Lumens
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



