

Project Name

Location

Prepared By



# SATCO S29911- TF

25T5/LED/46-850/DR/TF SHATTER

**Notes**

[www] 08-05-2020 22:44:01

**General**

Status	Active
Watts	25W
Incandescent Equivalent	100W
Fluorescent Equivalent	54W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	3500L
Beam Spread	185
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast required
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

**Physical**

MOL	48
MOD	0.63
Lens Finish	Gloss
Housing Color	None
Weight (lb.)	0.3

**Additional Information**

Includes	Integrated thermal fuse at pins
Integrated Features	Integrated thermal fuse at pins
Shatter-Proof Type	Yes
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5-Years

**Compliance**

Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp