

Notes

rw] 05-12-2025 02:4

General Status	Discontinued
Substitute	S49935R1
Watts	12W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	3500K
Temperature	Neutral White
CRI	80+
Lumens	1700L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Power Factor	0.9
Power Factor Operating Temperature	
	0.9
Operating Temperature	0.9
Operating Temperature  Physical	0.9 -20C (-4F) to +45C (+113F)
Operating Temperature  Physical  MOL	0.9 -20C (-4F) to +45C (+113F)
Operating Temperature  Physical  MOL  MOD	0.9 -20C (-4F) to +45C (+113F) 48 1
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information	0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures.
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty	0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status  Colorado Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status  Nevada Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status  Nevada Status  Vermont Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status  Nevada Status  Vermont Status  Washington Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status  Nevada Status  Vermont Status  Washington Status  RoHS Compliant	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lens Finish  Additional Information  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  DLC Approved  California Status  Title 20 / 24 Status  Colorado Status  Hawaii Status  Nevada Status  Vermont Status  Washington Status	0.9 -20C (-4F) to +45C (+113F)  48 1 Gloss  Not for use in vapor tight fixtures. 5-Years  cULus Damp No Lawful for sale in California Lawful for sale

