

Notes

w1 05-07-2025 00:4

General	
Status	Discontinued
Substitute	S49937R1
Watts	12W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	1800L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED
Electrical	
Dallacking Daguiyanaanta	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible
Ballasting Requirements	with every ballast. Refer to the ballast compatibility chart
Power Factor	with every ballast. Refer to the ballast
	with every ballast. Refer to the ballast compatibility chart
Power Factor	with every ballast. Refer to the ballast compatibility chart 0.9
Power Factor Operating Temperature	with every ballast. Refer to the ballast compatibility chart 0.9
Power Factor Operating Temperature Physical	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1
Power Factor Operating Temperature Physical MOL MOD Lens Finish	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.)	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years cULus
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp No
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp No Lawful for sale in California
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp No Lawful for sale in California Lawful for sale
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp No Lawful for sale in California Lawful for sale
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp No Lawful for sale in California Lawful for sale
Power Factor Operating Temperature Physical MOL MOD Lens Finish Weight (lb.) Additional Information Installation Notes Warranty Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	with every ballast. Refer to the ballast compatibility chart 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss 0.41 Not for use in vapor tight fixtures. 5 Years CULus Damp No Lawful for sale in California Lawful for sale Lawful for sale



LED_Lamp

SDS Sheet