

Project Name

Location

Prepared By



SATCO S29940

12T8/LED/48-840/DR-DM

Notes

(www) 05-13-2023 23:26:34

General

Status	Discontinued
Substitute	S49936R1
Watts	12W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W-32W
Volts	Ballast Dependent
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	1800L
Beam Spread	210
Dimmable	Yes-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	Ballast required. Direct Replacement- for use on Instant Start, Rapid Start, Emergency, and Dimming ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatability chart.
Dimming Note	Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	48
MOD	1
Lens Finish	Gloss

Additional Information

Installation Notes	Not for use in vapor tight fixtures.
Warranty	5-Years

Compliance

Safety Listing	cULus - Listed
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp