SATCO NUVO

General

Project Name

Location

Prepared By



SATCO S39055

8.5WLED/DW/EL/4/27K/120V

Notes

StatusActiveWattage8.5WVoltage120VFinishWhiteCCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output500LIndoor or Outdoor FixtureIndoorSpecificationsTechnologyLEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableDimmableYes-DimmableDimensions120V onlyWidth (in.)5Height (in.)1.94Weight (lb.)0.4ComplianceSafety Listing Location RatingCation RatingDamp	+113F)
Voltage120VFinishWhiteCCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output500LIndoor or Outdoor FixtureIndoorSpecificationsEEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableDimmableYes-DimmableDimmsions120V onlyWidth (in.)5Height (in.)1.94Weight (lb.)0.4Safety ListingcETLus - Listed	+113F)
FinishWhiteCCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output500LIndoor or Outdoor FixtureIndoorSpecificationsEEDTechnologyLEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableDimmableYes-DimmableDimming Note120V onlyDimensions1.94Width (in.)5Height (in.)0.4ComplianceSafety ListingCETLus - Listed	+113F)
CCT (Kelvin)2700KColor TemperatureWarm WhiteLumen Output500LIndoor or Outdoor FixtureIndoorSpecificationsTechnologyLEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableYes-DimmableDimensions120V onlyWidth (in.)5Height (in.)1.94Weight (lb.)0.4CompliancecETLus - Listed	+113F)
Color TemperatureWarm WhiteLumen Output500LIndoor or Outdoor FixtureIndoorSpecificationsEEDTechnologyLEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableYes-DimmableDimming Note120V onlyDimensions5Width (in.)5Height (in.)0.4ComplianceSafety ListingCETLus - Listed	+113F)
Lumen Output500LIndoor or Outdoor FixtureIndoorSpecificationsIndoorTechnologyLEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableDimmableYes-DimmableDimensions120V onlyWidth (in.)5Height (in.)1.94Weight (lb.)0.4ComplianceSafety ListingCETLus - Listed	+113F)
Indoor or Outdoor FixtureIndoorSpecificationsIEDTechnologyLEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableYes-DimmableDimming Note120V onlyDimensions5Width (in.)5Height (in.)1.94Weight (lb.)0.4ComplianceETLus - Listed	+113F)
SpecificationsTechnologyLEDCRI90+Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableYes-DimmableDimming Note120V onlyDimensions5Width (in.)5Height (in.)0.4Weight (lb.)0.4Safety ListingcETLus - Listed	+113F)
Technology LED CRI 90+ Beam Angle 100 Rated Hours 40000 Operating Temperature -20C (-4F) to +45C (D) Dimmable Yes-Dimmable Dimming Note 120V only Dimensions 1.94 Width (in.) 1.94 Height (ib.) 0.4 Safety Listing cETLus - Listed	+113F)
Initial System Initial System CRI 90+ Beam Angle 100 Rated Hours 40000 Operating Temperature -20C (-4F) to +45C (Dimmable Yes-Dimmable Dimming Note 120V only Dimensions 120V only Width (in.) 5 Height (in.) 0.4 Compliance ETLus - Listed	+113F)
Beam Angle100Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableYes-DimmableDimming Note120V onlyDimensionsWidth (in.)5Height (in.)1.94Weight (lb.)0.4ComplianceSafety ListingcETLus - Listed	+113F)
Rated Hours40000Operating Temperature-20C (-4F) to +45C (DimmableYes-DimmableDimming Note120V onlyDimensions120V onlyWidth (in.)5Height (in.)1.94Weight (lb.)0.4ComplianceETLus - Listed	+113F)
Operating Temperature -20C (-4F) to +45C (Dimmable Yes-Dimmable Dimming Note 120V only Dimensions 120V only Width (in.) 5 Height (in.) 1.94 Weight (lb.) 0.4 Compliance ETLus - Listed	+113F)
Dimmable Yes-Dimmable Dimming Note 120V only Dimensions 5 Width (in.) 5 Height (in.) 1.94 Weight (lb.) 0.4 Compliance 5 Safety Listing cETLus - Listed	+113F)
Dimming Note 120V only Dimensions 5 Width (in.) 5 Height (in.) 1.94 Weight (lb.) 0.4 Compliance 5 Safety Listing cETLus - Listed	
Dimensions Width (in.) 5 Height (in.) 1.94 Weight (lb.) 0.4 Compliance 5 Safety Listing cETLus - Listed	
Width (in.) 5 Height (in.) 1.94 Weight (lb.) 0.4 Compliance Safety Listing cETLus - Listed	
Height (in.) 1.94 Weight (lb.) 0.4 Compliance Safety Listing CETLus - Listed	
Weight (lb.) 0.4 Compliance Safety Listing cETLus - Listed	
Compliance Safety Listing CETLus - Listed	
Safety Listing CETLus - Listed	
, , ,	
Location Rating Damp	
Energy Star No	
DLC Approved No	
Air Tight Rated Yes	
IC Rated Yes	
California Status Lawful for sale in Ca	lifornia
Title 20 / 24 Status California T24 Listed	
California Prop 65 Lead	
RoHS Compliant Yes	
FCC Compliant Yes	
SDS Sheet LED_Lamp	
Additional Information	

Warranty

5 Year Limited - Fixtures

