

Project Name

Location

Prepared By



## SATCO S39750

30W/LED/HID/MB-G3/50K/100-277V

### Notes

(www) 04-30-2023 00:43:57

### General

|                         |   |
|-------------------------|---|
| Status                  | Active  |
| Watts                   | 30W   |
| Incandescent Equivalent | 200W  |
| Fluorescent Equivalent  | 55W   |
| HID Equivalent          | 150W  |
| Volts                   | 120V-277V   |
| Shape                   | Corn cob  |
| Base                    | Medium  |
| ANSI Base               | E26   |
| Finish                  | Clear   |
| CCT (Kelvin)            | 5000K   |
| Temperature             | Natural Light                                     |
| CRI                     | 80+   |
| Lumens                  | 4200L   |
| Beam Spread             | 120/150/260                                       |
| Dimmable                | Non-Dimmable                                      |
| Hours Rated             | 50000   |
| Product Category        | LED HID   |
| Technology              | LED   |
| Min Compartment Size    | Width: 8.00 in. Depth: 8.00 in. Height: 11.00 in. |
| Ballasting Requirements | Ballast Bypass                                    |

### Electrical

|                       |                                 |
|-----------------------|---------------------------------|
| Operating Frequency   | 50/60Hz                         |
| Power Factor          | 0.98                            |
| Operating Position    | Universal                       |
| Surge Protection      | Built-in surge protection - 4KV |
| Operating Temperature | -20C (-4F) to +65C (+149F)      |

### Physical

|                     |                      |
|---------------------|----------------------|
| MOL                 | 6.69                 |
| MOD                 | 3.31                 |
| Lens Finish         | Clear                |
| Lens Material       | Thermo Plastic (PBT) |
| Housing Color       | White                |
| Photocell or Sensor | Optional Add-On      |
| Weight (lb.)        | 1.37                 |

### Additional Information

|                            |   |
|----------------------------|---|
| Additional Info            | PIR Sensor available as an accessory          |
| Rated For Enclosed Fixture | Yes   |
| IP Rating                  | IP64  |
| Specification Note         | Closed 260 deg; Partial 150 deg; Open 120 deg |
| Installation Notes         | Not for use in vapor tight fixtures.          |
| Warranty                   | 5 Years                                       |

### Compliance

|                      |   |
|----------------------|---|
| Safety Listing       | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating      | Damp  |
| DLC Approved         | No  |
| California Status    | Lawful for sale in California                         |
| Title 20 / 24 Status | Lawful for sale                                       |
| Colorado Status      | Lawful for sale                                       |
| Hawaii Status        | Lawful for sale                                       |
| Nevada Status        | Lawful for sale                                       |
| Vermont Status       | Lawful for sale                                       |
| Washington Status    | Lawful for sale                                       |
| RoHS Compliant       | Yes   |
| FCC Compliant        | Yes   |
| SDS Sheet            | LED_Lamp  |