## SATCO NUVO

Project Name

ocation

Prepared By



Notes

rw1 08-26-2025 22:39:

| General                 |  |
|-------------------------|--|
| Status                  | Active   |
| Watts                   | 60W  |
| Incandescent Equivalent | 500W   |
| Fluorescent Equivalent  | 85W  |
| HID Equivalent          | 250W   |
| Volts                   | 120V-277V  |
| Shape                   | Corncob  |
| Base                    | Mogul Extended                                   |
| ANSI Base               | EX39   |
| Finish                  | Clear  |
| CCT (Kelvin)            | 2700K  |
| Temperature             | Warm White                                       |
| CRI                     | 80+  |
| Lumens                  | 7680L  |
| Beam Spread             | 120/150/260                                      |
| Dimmable                | Non-Dimmable                                     |
| Hours Rated             | 50000  |
| Product Category        | LED HID  |
| Technology              | LED  |
| Min Compartment Size    | Width: 9.30 in. Depth: 9.30 in. Height: 9.80 in. |
| Ballasting Requirements | Ballast Bypass                                   |
| Electrical              |  |

| Electrical            |                                 |  |
|-----------------------|---------------------------------|--|
| Operating Frequency   | 50/60Hz                         |  |
| Power Factor          | >0.9                            |  |
| Operating Position    | Base Up or Down                 |  |
| Surge Protection      | Built-in surge protection - 4KV |  |
| THD                   | <20%                            |  |
| Operating Temperature | -20C (-4F) to +65C (+149F)      |  |

| Physical            |                      |
|---------------------|----------------------|
| MOL                 | 7.76                 |
| MOD                 | 4.08                 |
| Lens Finish         | Clear                |
| Lens Material       | Thermo Plastic (PBT) |
| Housing Color       | White                |
| Photocell or Sensor | Optional Add-On      |
| Weight (lb.)        | 2.05                 |

| Additional Information     |   |
|----------------------------|---|
| Additional Info            | PIR Sensor available as an accessory          |
| Rated For Enclosed Fixture | Yes   |
| IP Rating                  | IP64  |
| Specification Note         | Closed 260 deg; Partial 150 deg; Open 120 deg |
| Installation Notes         | Not for use in vapor tight fixtures.          |
| Warranty                   | 5-Years                                       |

| Compliance           |  |
|----------------------|--|
| Safety Listing       | cULus - Certified; cULus - Classified; cULus -<br>Listed |
| Location Rating      | Damp   |
| DLC Approved         | No   |
| California Status    | Lawful for sale in California                            |
| Title 20 / 24 Status | Lawful for sale  |
| Colorado Status      | Lawful for sale  |
| Hawaii Status        | Lawful for sale  |
| Nevada Status        | Lawful for sale  |
| Vermont Status       | Lawful for sale  |
| Washington Status    | Lawful for sale  |
| RoHS Compliant       | Yes  |
| FCC Compliant        | Yes  |
| SDS Sheet            | LED_Lamp   |