SATCO NUVO

Project Name

ocation Prepared By



Notes

1 06-23-2025 00:03:4

Status Discontinued Substitute S49977R1 Watts 15W Incandescent Equivalent 100W Fluorescent Equivalent 25W-32W Volts Ballast Dependent Ballast Type Type A Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dnly in Type A mode; Check Ballast MFG for Dimmer Compatibility Chart MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California		
Substitute S49977R1 Watts 15W Incandescent Equivalent 100W Fluorescent Equivalent 25W-32W Volts Ballast Dependent Ballast Type Type A Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0,9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compilance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Lawful for sale Cities Title 20 / 24 Status Cities Title 20 / 24 Statu	General	
Watts 15W Incandescent Equivalent 100W Fluorescent Equivalent 25W-32W Volts Ballast Dependent Ballast Type Type A Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements application on rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compilance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Status	Discontinued
Incandescent Equivalent Fluorescent Equivalent Fluorescent Equivalent Volts Ballast Dependent Ballast Type Type A Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length Flinish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI Beam Spread 210 Dimmable Hours Rated Forduct Category Linear Technology LED Flectrical Ballasting Requirements Ballasting Requirements Ballasting Requirements Dimming Note Dimming Note Dimming Note Physical MOL A48 MOD 1 Lens Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Chart Dimming Note Dimming Note The Cool of	Substitute	S49977R1
Fluorescent Equivalent Volts Ballast Type Type A Type A Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI Bamaspread 2200L Beam Spread 210 Dimmable Yes-Dimmable Ves-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements Ballasting Requirements Ballasting Requirements Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor Operating Temperature Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty Compliance Safety Listing Cullus Culfornia Status Lawful for sale	Watts	15W
Volts Ballast Type Type A Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode: Check Ballast MFG for Dimmer Compatibility Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Lawful for sale in California Title 20 / 24 Status Lawful for sale Installation Inclifornia Title 20 / 24 Status Lawful for sale Installation Inclifornia Title 20 / 24 Status Lawful for sale	Incandescent Equivalent	100W
Ballast Type Type A Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatibile with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale	Fluorescent Equivalent	25W-32W
Shape T8 Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compilance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale Title 20 / 24 Status Lawful for sale Title 20 / 24 Status Lawful for sale Title 20 / 24 Status Lawful for sale	Volts	Ballast Dependent
Base Medium Bi Pin ANSI Base G13 Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compiliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale Title 20 / 24 Status Lawful for sale Installation Status Title 20 / 24 Status Lawful for sale Lawful for sale	Ballast Type	Type A
ANSI Base Nominal Length A8 Finish Gloss White CCT (Kelvin) Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Product Category Linear Technology LED Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimming Note Dimmer Compatibility Power Factor Operating Temperature Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compiliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Title 20 / 24 Status Lawful for sale Installation Information No California Status Lawful for sale	Shape	Т8
Nominal Length 48 Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale Installation Status Lawful for sale	Base	Medium Bi Pin
Finish Gloss White CCT (Kelvin) 4000K Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Flectrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	ANSI Base	G13
CCT (Kelvin) Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated Product Category Technology LID Ballasting Requirements Ballasting Requirements Ballasting Requirements Ballasting Requirements Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimmer Compatibility Power Factor Operating Temperature Operating Temperature Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Rated For Enclosed Fixture Ves Warranty Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Nominal Length	48
Temperature Cool White CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Chart Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Finish	Gloss White
CRI 80+ Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballasting Requirements Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale	CCT (Kelvin)	4000K
Lumens 2200L Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Flectrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale	Temperature	Cool White
Beam Spread 210 Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale	CRI	80+
Dimmable Yes-Dimmable Hours Rated 50000 Product Category Linear Technology LED Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale		
Hours Rated Product Category Technology Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor Operating Temperature Ou.9 Operating Temperature Ou.9 Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Rated For Enclosed Fixture Warranty 5-Years Compliance Safety Listing Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	· · · · · · · · · · · · · · · · · · ·	
Product Category Technology Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor O.9 Operating Temperature Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale		
Electrical Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor Operating Temperature Operating Temperature Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty S-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale		
Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale		
Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Dimming Note Power Factor Operating Temperature Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing Location Rating Damp DLC Approved All Information California Lawful for sale in California Title 20 / 24 Status Lawful for sale Installation California Lawful for sale	Technology	LED
on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatible with every ballast. Refer to the ballast compatibility chart Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Yes Warranty 5-Years Compliance Safety Listing Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Not For use in vapor tight fixtures. Ves Lawful for sale in California Lawful for sale	Electrical	
Dimming Note Only in Type A mode; Check Ballast MFG for Dimmer Compatibility Power Factor 0.9 Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Yes Warranty 5-Years Compliance Safety Listing Location Rating Damp DLC Approved California Status Lawful for sale in California Title 20 / 24 Status		Dallact required Direct Depleasement for use
Operating Temperature -20C (-4F) to +45C (+113F) Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing Location Rating Damp DLC Approved No California Status Lawful for sale Lawful for sale	Ballasting Requirements	on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast
Physical MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale		on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for
MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing cULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status	Dimming Note	on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
MOL 48 MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing cULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status	Dimming Note Power Factor	on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9
MOD 1 Lens Finish Gloss White Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature	on Instant Start and Rapid Start ballasts with no rewiring required.May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9
Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty 5-Years Compliance Safety Listing Location Rating DLC Approved California Status Lawful for sale Closs White Note for use in vapor tight fixtures. Yes Ves Utus Location Rating Damp Location Rating Lawful for sale in California Lawful for sale	Dimming Note Power Factor Operating Temperature Physical	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F)
Additional Information Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing CULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F)
Installation Notes Rated For Enclosed Fixture Warranty 5-Years Compliance Safety Listing Location Rating DLC Approved California Status Title 20 / 24 Status Not for use in vapor tight fixtures. Yes Culus LULus Lawful for sale in California Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F)
Rated For Enclosed Fixture Warranty 5-Years Compliance Safety Listing Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F)
Warranty 5-Years Compliance Safety Listing cULus Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White
Compliance Safety Listing Location Rating Damp DLC Approved No California Status Little 20 / 24 Status CULus Damp Damp Lawful for sale in California Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures.
Safety Listing Location Rating Damp DLC Approved No California Status Lawful for sale in California Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes
Location Rating Damp DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes
DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes
California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years
Title 20 / 24 Status Lawful for sale	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years cULus Damp
	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years cULus Damp No
	Dimming Note Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Installation Notes Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating DLC Approved California Status	on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.9 -20C (-4F) to +45C (+113F) 48 1 Gloss White Not for use in vapor tight fixtures. Yes 5-Years CULus Damp No Lawful for sale in California

Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED Lamp