

Project Name

Location Prepared By



**SATCO S8531** 

9WPLH/LED/830/BP/2P

Notes

Status	Active	
Watts	9W	
Fluorescent Equivalent	18W/26W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	PL	
Base	G24d (2-Pin)	
ANSI Base	G24d	
Finish	Frost	
CCT (Kelvin)	3000K	
Temperature	Warm White	
CRI	82	
Lumens	950L	
Beam Spread	120	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	PL	
Operating Position	Horizontal	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	6.63
MOD	1.09
Weight (lb.)	0.14

Additional Information	
Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance	
Safety Listing	cULus - Classified; cULus - Certified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp