

Project Name

Location Prepared By



Notes

www] 01-15-2024 02:40:1

Caraval	
General	
Status	Discontinued
Substitute	S49936
Watts	11.5W
Incandescent Equivalent	60W
Fluorescent Equivalent	25W-32W
Ballast Type	Туре А
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	82
Lumens	1800L
Beam Spread	220
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	May not be compatible with all rapid start, dimmable, and emergency ballasts.; Ballast required; Direct Replacement-for
	use on Instant Start and Rapid Start ballasts with no rewiring required
Dimming Note	Start ballasts with no rewiring
Dimming Note Power Factor	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer
	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility
Power Factor Operating Temperature	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96
Power Factor Operating Temperature Physical	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD Lens Finish	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating Energy Star	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp No
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp No No
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp No No Exempt - Base Not Regulated
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp No No Ro Exempt - Base Not Regulated Lawful for sale in California
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp No No Exempt - Base Not Regulated Lawful for sale Lawful for sale
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status Colorado Status	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp No No Exempt - Base Not Regulated Lawful for sale Lawful for sale Lawful for sale
Power Factor Operating Temperature Physical MOL MOD Lens Finish Additional Information Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status Title 20 / 24 Status	Start ballasts with no rewiring required Only in Type A mode; Check Ballast MFG for Dimmer Compatibility 0.96 -20C (-4F) to +45C (+113F) 48 1 Gloss White 5 Year Limited - T8 LED Bulbs cULus Damp No No Exempt - Base Not Regulated Lawful for sale Lawful for sale

Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



