

Project Name

Location Prepared By



Notes

rw] 02-05-2025 01:2

Status	Active	
Watts	15W	
Fluorescent Equivalent	36W	
Volts	120V-277V	
Ballast Type	Туре В	
Shape	T5	
Base	2G11	
ANSI Base	2G11	
Finish	Frost	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80	
Lumens	2000L	
Beam Spread	270	
Dimmable	Non-Dimmable	
Hours Rated	50000	
Product Category	PL	
Operating Position	Universal	
Technology	LED	

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20% (+/-5%)
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical	
MOL	16.5
MOD	0.68
Housing Color	White
Weight (lb.)	0.31

Additional Information	
Additional Info	CCT Selectable Option: S18422
Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance	
Safety Listing	cULus
Location Rating	Damp
DLC Approved	No
NSF Approved	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Yes
SDS Sheet	LED Lamp