SATCO NUVO

Project Name

Prepared By



NUVO TH412

12W LED TRACK HEAD PINCH BACK

Notes

StatusActiveTypeTrack HeadTypeTrack HeadWattage12WFinishBlackBeam Angle24CCT (Kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecifications90+CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimmig Note20V onlyWeight (Ib.)1.05Dimensions2.88Ketnesion (in.)3.63Extension (in.)5.5Safety ListingCFLus - ListedLocation RatingDryUL ApplicationTrackDiCApprovedNoCalifornia StatusLawful for sale in CaliforniaClifornia StatusLawful for sale in CaliforniaClifornia Frop 65LeadRoHS CompliantYesConcopliant Standard ICES-005Class BSDS SheetLED_Fixture	General	
And Wattage12WFinishBlackBeam Angle24CCT (kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsCRIQU90+Lumen Output1020LRated Hours30000Voltage120VDinmableYes-DinmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Langth (in.)3.63Extension (in.)5.5ComplianceSet Lus - ListedLocation RatingDryUL ApplicationTrackENREGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Status	Active
IntegrationBlackBeam Angle24CCT (Kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecifications90+CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05Dimensions2.88Height (in.)2.88Langth (in.)3.63Extension (in.)5.5ComplianceDryUL ApplicationTrackENRGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Туре	Track Head
Beam Angle24CCT (Kelvin)3000KCTT (Kelvin)3000KCTT (Kelvin)3000KBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsSecondCRI90+Lumen Output1020LRated Hours30000Voltage20VDimmableYes-DinmableDimming Note120V onlyWeight (lb.)1.05Dimensions2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSetTLus - ListedLocation RatingDryUL ApplicationTrackENRGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC Compliant ICES-005Class B	Wattage	12W
CT (Kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsSpecificationsCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05Dimensions2.88Length (in.)2.88Length (in.)5.5ComplianceSolonSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENRGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Finish	Black
TemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsIndoorCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05Dimensions2.88Height (in.)2.88Extension (in.)5.5ComplianceSoloSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackNoCalifornia StatusLaght for a SatusCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCandian Standard ICES-005Class B	Beam Angle	24
BaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecifications90+CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (Ib.)1.05Dimensions2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceVoltageSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	CCT (Kelvin)	3000К
ANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecifications90+CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (Ib.)1.05DimensionsHeight (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingLocation RatingDryUL ApplicationTrackENREGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusYesFCC CompliantYesFCC CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Temperature	Warm White
IndoorIndoorSpecifications90+CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (Ib.)1.05Dimensions2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceUutup (Ibulance)Safety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia National (ICES-005)Class B	Base	Integrated
SpecificationsCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DinmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceDirySafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	ANSI Base	Integrated
CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Indoor or Outdoor Fixture	Indoor
Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceESafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Specifications	
Rated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	CRI	90+
Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Lumen Output	1020L
DimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Rated Hours	30000
Dimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Voltage	120V
Weight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Dimmable	Yes-Dimmable
DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Dimming Note	120V only
Height (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Weight (lb.)	1.05
Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Dimensions	
Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Height (in.)	2.88
Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Width (in.)	2.88
ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Length (in.)	3.63
Safety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Extension (in.)	5.5
Location RatingDryLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Compliance	
UL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	Safety Listing	cETLus - Listed
ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class B	Location Rating	Dry
DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class B	UL Application	Track
California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class B	ENERGY STAR	No
Title 20 / 24 Status California T24 Listed California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class B	DLC Approved	No
California Prop 65 Lead RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class B	California Status	Lawful for sale in California
RoHS Compliant Yes FCC Compliant Yes Canadian Standard ICES-005 Class B	Title 20 / 24 Status	California T24 Listed
FCC Compliant Yes Canadian Standard ICES-005 Class B	California Prop 65	Lead
Canadian Standard ICES-005 Class B	RoHS Compliant	Yes
	FCC Compliant	Yes
SDS Sheet LED_Fixture	Canadian Standard ICES-005	Class B
	SDS Sheet	LED_Fixture

Additional Information Warranty

5 Years

