

Project Name

Location Prepared By



Notes

General	
Status	Active
Fixture Type	Strip Light
Finish	White
Wattage	30W/40W/50W
Lumen Output	3900L-6750L
CCT (Kelvin)	3500K/4000K/5000K
IP Rating	IP20
Smart Product Info	

Finish	White
Wattage	30W/40W/50W
Lumen Output	3900L-6750L
CCT (Kelvin)	3500K/4000K/5000K
IP Rating	IP20
Smart Product Info	
IOT Enabled	No
Specifications	
Technology	LED
Color Temperature	Neutral White to Daylight
CRI	80
Voltage	120V-277V
Beam Angle	120
Rated Hours	50000
Operating Temperature	-20C (-4F) to +60C (+140F)
Dimmable	Yes-Dimmable
Dimming Note	0-10V Dimming
Photocell or Sensor	Has Photocell
Lens Material	Polycarbonate (PC)
Surge Protection	Built-in surge protection - 2KV
Weight (lb.)	4.41
Material	Steel
Dimensions	
Height (in.)	3.27
Width (in.)	2.95
Length (in.)	48
Back Plate or Canopy Diameter (in.)	4.75

Compliance	
Safety Listing	cULus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	S-XSNARP
B.U.G. Rating	B2-U4-G2
NSF Approved	No
CA T20 / T24 Rationale	T20 Exempt - Fixtures Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Flicker Free	Yes
SDS Sheet	LED_Fixture

Additional Information

Additional Information

EM Mode 4W/90 Min run time.
Other DLC Listings: S-UZ1QD6,
Standard, Direct Linear Ambient
Luminaires.

Warranty

5 Year Limited - Fixtures

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



