## SATCO NUVO

Project Name

Location

Prepared By



## **SATCO S11394**

4.5MR16/LED/40'/840/12V

Notes

www] 01-15-2024 02:40:

General	
Status	Active
Watts	4.5W
Incandescent Equivalent	35W
Volts	12V
Shape	MR16
Base	Bi Pin GU5.3
ANSI Base	GU5.3
Finish	Gray
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	360L
Beam Spread	40
Dimmable	Yes-Dimmable
Dimming Note	Check the transformer/driver MFG for dimmer compatibility
Hours Rated	25000
Lamp Type	MR
Technology	LED
Electrical	
Operating Frequency	60Hz
CBCP	730
Candlepower	730
Power Factor	0.94
1 OWCI I doloi	0.01
Operating Temperature	-25C (-13F) to +45C (+113F)
Operating Temperature	
Operating Temperature  Physical	-25C (-13F) to +45C (+113F)
Operating Temperature  Physical  MOL	-25C (-13F) to +45C (+113F)
Operating Temperature  Physical  MOL  MOD	-25C (-13F) to +45C (+113F)  1.77  1.97
Operating Temperature  Physical  MOL  MOD  Lensed	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day  cULus  Damp
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day  CULus  Damp  No
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  CA T20 / T24 Rationale	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day  cULus  Damp  No  T20 Listed
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  CA T20 / T24 Rationale  California Status	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day  cULus  Damp  No  T20 Listed  Lawful for sale in California
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  CA T20 / T24 Rationale  California Status  Title 20 / 24 Status	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day  CULus  Damp  No  T20 Listed  Lawful for sale in California  Lawful for sale
Operating Temperature  Physical  MOL  MOD  Lensed  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Rated For Enclosed Fixture  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  CA T20 / T24 Rationale  California Status  Title 20 / 24 Status  RoHS Compliant	-25C (-13F) to +45C (+113F)  1.77  1.97  Lensed Lamp  Array  Plastic  Gray  0.08  Yes  5 Year Limited - 10 hr per day  CULus  Damp  No  T20 Listed  Lawful for sale in California  Lawful for sale  Yes

All Rights Reserved

https://www.satco.com/



