SATCO NUVO

Project Name

ocation Prepared By



10.5A19/LED/827/AGRI/120V/D

Notes

StatusActiveWatts10.5WIncandescent Equivalent100WVolts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimmable25000Product CategoryType ATechnologyEDEtertical2000 (4F) (4F) (4F) (4F) (4F) (4F) (4F) (4F)	General	
Incandescent Equivalent100WVolts120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimms Rated25000Product CategoryType ATechnologyEDElectrical0.9Operating Frequency60HzPower Factor0.9Operating Temperature2.36MOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationYesRated For Enclosed FixtureYesSafety ListingCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Status	Active
Voits120VShapeA19BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimmable25000Product CategoryType ATechnologyEDElectrical-20C (-4F) to +45C (+113F)Physical.20S (-4F) to +45C (+113F)Physical.20S (-4F) to +45C (+113F)MOL4.61MOD2.36Housing ColorWhiteWeight (Ib.)0.14Additional InformationYesSafety ListingCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantRued For Enclosed FixtureYesSafety ListingCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Watts	10.5W
ShapeA19BaseMediumANSI BaseE26FinishFrostCCT (kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimmableYes-DimmableDimmable25000Product CategoryType ATechnologyLEDElectrical25000Operating Frequency60HzOperating Temperature0.9Operating Temperature-20C (-4F) to +45C (+113F)Physical4.61MOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationYesRated For Enclosed FixtureYesSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRotS CompliantYesFCCYesFCCYesFCCYes	Incandescent Equivalent	100W
BaseMediumANSI BaseE26FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DinmableYes-DinmableDinming Note120V onlyHours Rated25000Product CategoryType ATechnologyEEDElectricalUOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalUMOL4.61MoD2.36Housing ColorWhiteWeight (Ib.)0.14Additional InformationYesRated For Enclosed FixtureYesSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCCYes	Volts	120V
ANSI BaseE26FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimmable25000Product CategoryType ATechnologyEEDElectrical0.9Operating Frequency60HzPower Factor0.9Operating ColorWhiteMOL4.61MOD2.36Housing ColorWhiteWeight (Ib.)0.14Additional InformationYesRated For Enclosed FixtureYesSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantFCC CompliantYesFCC CompliantYes	Shape	A19
FinishFrostCCT (Kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimming Note120V onlyHours Rated25000Product CategoryType ATechnologyEDElectrical9Operating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)Physical4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional Information5-YearsComplianceYesSafety ListingCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Base	Medium
CCT (Kelvin)2700KTemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimming Note120V onlyHours Rated25000Product CategoryType ATechnologyEEDElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (Ib.)0.14Additional Information5-YearsComplianceSafety ListingCucation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantFCC CompliantYesFCC CompliantYes	ANSI Base	E26
TemperatureWarm WhiteCRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimming Note120V onlyHours Rated25000Product CategoryType ATechnologyLEDElectrical9000Operating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)Physical4.61MOL4.61MOD2.36Housing ColorWhiteWeight (Ib.)0.14Additional Information5-YearsComplianceSafety ListingCullus - ListedLocation RatingCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantFCC CompliantYes	Finish	Frost
CRI80+Lumens1600LBeam Spread140DimmableYes-DimmableDimming Note120V onlyHours Rated25000Product CategoryType ATechnologyLEDElectrical0.9Operating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOLMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcLLus - ListedLocation RatingWetCalifornia StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	CCT (Kelvin)	2700K
Lumens1600LBeam Spread140DimmableYes-DimmableDimming Note120V onlyHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Rated For Enclosed FixtureYesSafety ListingCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Temperature	Warm White
Beam Spread140DimmableYes-DimmableDimming Note120V onlyHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationYesSafety ListingCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	CRI	80+
DimmableYes-DimmableDimming Note120V onlyHours Rated25000Product CategoryType ATechnologyLEDElectrical0.9Operating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOLMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Lumens	1600L
Dimming Note120V onlyHours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Rated For Enclosed FixtureYesWarranty5-YearsComplianceCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRotS CompliantYesFCC CompliantYes	Beam Spread	140
Hours Rated25000Product CategoryType ATechnologyLEDElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationYesRated For Enclosed FixtureYesSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Dimmable	Yes-Dimmable
Product CategoryType ATechnologyLEDElectricalElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)Physical4.61MOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Dimming Note	120V only
TechnologyLEDElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Hours Rated	25000
ElectricalOperating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Product Category	Туре А
Operating Frequency60HzPower Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalImage: Construct of the state of the sta	Technology	LED
Power Factor0.9Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Electrical	
Operating Temperature-20C (-4F) to +45C (+113F)PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationYesRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Operating Frequency	60Hz
PhysicalMOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Power Factor	0.9
MOL4.61MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceULus - ListedSafety ListingCULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Operating Temperature	-20C (-4F) to +45C (+113F)
MOD2.36Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Physical	
Housing ColorWhiteWeight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	MOL	4.61
Weight (lb.)0.14Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	MOD	2.36
Additional InformationRated For Enclosed FixtureYesWarranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Housing Color	White
Rated For Enclosed Fixture Yes Warranty 5-Years Compliance Safety Listing cULus - Listed Location Rating Wet California Status Non-Compliant Title 20 / 24 Status Non-Compliant RoHS Compliant Yes FCC Compliant Yes	Weight (lb.)	0.14
Warranty5-YearsComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Additional Information	
ComplianceSafety ListingcULus - ListedLocation RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Rated For Enclosed Fixture	Yes
Safety Listing cULus - Listed Location Rating Wet California Status Non-Compliant Title 20 / 24 Status Non-Compliant RoHS Compliant Yes FCC Compliant Yes	Warranty	5-Years
Location RatingWetCalifornia StatusNon-CompliantTitle 20 / 24 StatusNon-CompliantRoHS CompliantYesFCC CompliantYes	Compliance	
California Status Non-Compliant Title 20 / 24 Status Non-Compliant RoHS Compliant Yes FCC Compliant Yes	Safety Listing	cULus - Listed
Title 20 / 24 Status Non-Compliant RoHS Compliant Yes FCC Compliant Yes	Location Rating	Wet
RoHS Compliant Yes FCC Compliant Yes	California Status	Non-Compliant
FCC Compliant Yes	Title 20 / 24 Status	Non-Compliant
	RoHS Compliant	Yes
SDS Sheet LED_Lamp	FCC Compliant	Yes
	SDS Sheet	LED_Lamp

