

Project Name

Location

Prepared By



Notes

[www] 05-15-2024 04:42:54

General

Status	Active
Watts	3W
Incandescent Equivalent	25W
Fluorescent Equivalent	6W
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	Miniature Bi Pin
ANSI Base	G5
Nominal Length	9
Finish	Frost
CCT (Kelvin)	6500K
Temperature	Daylight
CRI	82
Lumens	270L
Beam Spread	240
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	Linear
Technology	LED

Electrical

Ballasting Requirements	No ballast or external driver required
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20%
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical

MOL	8.91
MOD	0.83
Material	Glass
Lens Finish	Frost
Weight (lb.)	0.06

Additional Information

Additional Info	Replaces F6T5/D lamps
Shatter-Proof Type	PET Coated
Installation Notes	Not for use in vapor tight fixtures. Direct wire 120-277V line voltage; Double ended wiring
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - T5 LED Bulbs - Ballast Bypass

Compliance

Safety Listing	cULus - Classified; cULus - Certified; ETLus - SANITATION RECOGNIZED COMPONENT
Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc.
All Rights Reserved

For More Information Visit:
<https://www.satco.com/>

