		<b>SATCO NUVO</b>
Project Name		
Location	Prepared By	
	1	
55×11		
70.		
SATCO S11912 11.5T8/LED/48-840/LF/BP		

Notes

rw1 10-27-2025 05:20:50

General		
Status	Active	
Watts	11.5W	
Incandescent Equivalent	50W	
Fluorescent Equivalent	32W	
Volts	120V-277V	
Ballast Type	Type B	
Shape	T8	
Base	Medium Bi Pin	
ANSI Base	G13	
Nominal Length	48	
Finish	White	
CCT (Kelvin)	4000K	
Temperature	Cool White	
CRI	80+	
Lumens	1750L	
Beam Spread	180	
Hours Rated	50000	
Product Category	Linear	
Technology	LED	
Electrical		
Dellastia a Demoissana anta	Ballast Bypass; Direct wire 120-277V line	
Ballasting Requirements	voltage; No ballast or external driver required	
Operating Frequency	50/60Hz	
Power Factor	0.9	
THD	20%	
Operating Temperature	-20C (-4F) to +45C (+113F)	
Physical		
MOL	47.78	
MOD	1	
Material	Glass	
Lens Finish	White	
Lens Material	Glass	
Housing Color	White	
Weight (lb.)	0.47	
Additional Information		
Additional Info	Installation protection - will not light if ballast	
Chatter Broof Type	is not bypassed. PET Coated	
Shatter-Proof Type	Not for use in vapor tight fixtures. Two	
Installation Notes	Installation Options - 1. Double Ended Wiring or 2. Single Ended Wiring	
Rated For Enclosed Fixture	Yes	
Warranty	5-Years	
Compliance		
Safety Listing	cULus - Classified; cULus - Certified; cRUus - Recognized Component; ETLus - Sanitation Recognized Component	
Location Rating	Damp	
DLC Approved	Yes	
DLC ID	PL20XAZLMN46	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
Colorado Status	Lawful for sale	
Hawaii Status	Lawful for sale	
Nevada Status	Lawful for sale	
Vermont Status	Lawful for sale	
Washington Status	Lawful for sale	
RoHS Compliant	Yes	
FCC Compliant	Yes	
NSF Approved	ETL Sanitation listed (conforms to NSF)	



Yes LED\_Lamp

Flicker Free

SDS Sheet