## SATCO NUVO

Project Name

Location Prepared By



Notes

ww] 05-15-2024 04:42:

0	
General	
Status	Active
Substitute	S13182
Watts	16W
Incandescent Equivalent	125W
Fluorescent Equivalent	32W
HID Equivalent	70W
Volts	120V-277V
Shape	ED23
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	2000L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	25000
Product Category	LED HID
Technology	LED
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Operating Position Operating Temperature	Universal -30C (-22F) to +65C (+149F)
Operating Temperature	
Operating Temperature  Physical	-30C (-22F) to +65C (+149F)
Operating Temperature  Physical  MOL	-30C (-22F) to +65C (+149F)
Operating Temperature  Physical  MOL  MOD	-30C (-22F) to +65C (+149F)  7.28  2.95
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material	-30C (-22F) to +65C (+149F)  7.28  2.95  White
Operating Temperature  Physical  MOL  MOD  Lens Finish	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)	-30C (-22F) to +65C (+149F)  7.28  2.95  White  Glass  White
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information	-30C (-22F) to +65C (+149F)  7.28 2.95 White Glass White 0.28
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info	-30C (-22F) to +65C (+149F)  7.28  2.95  White  Glass  White  0.28  HI-PRO Filament 120-277V
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture	-30C (-22F) to +65C (+149F)  7.28 2.95 White Glass White 0.28  HI-PRO Filament 120-277V Yes
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating	-30C (-22F) to +65C (+149F)  7.28 2.95 White Glass White 0.28  HI-PRO Filament 120-277V Yes IP65
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass White 0.28  HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures.
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty	-30C (-22F) to +65C (+149F)  7.28  2.95  White  Glass  White  0.28  HI-PRO Filament 120-277V  Yes  IP65
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass White 0.28  HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures.
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty  Compliance  Safety Listing	-30C (-22F) to +65C (+149F)  7.28  2.95  White  Glass  White  0.28  HI-PRO Filament 120-277V  Yes  IP65  Not for use in vapor tight fixtures.  3 Year Limited - 12 hr per day  cULus - Listed
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating	-30C (-22F) to +65C (+149F)  7.28 2.95 White Glass White 0.28  HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day  CULus - Listed Wet
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  Energy Star	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass White 0.28  HI-PRO Filament 120-277V  Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day  CULus - Listed Wet No
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass White 0.28  HI-PRO Filament 120-277V  Yes IP65  Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day  CULus - Listed  Wet No No
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved  CA T20 / T24 Rationale	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass White 0.28  HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day  CULus - Listed Wet No No No No No-Compliant - <82 CRI
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved  CA T20 / T24 Rationale  California Status	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass White 0.28  HI-PRO Filament 120-277V  Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day  CULus - Listed  Wet No No No No Non-Compliant - <82 CRI Non-Compliant
Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material  Housing Color  Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture  IP Rating  Installation Notes  Warranty  Compliance  Safety Listing  Location Rating  Energy Star  DLC Approved  CA T20 / T24 Rationale	-30C (-22F) to +65C (+149F)  7.28  2.95  White Glass White 0.28  HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day  CULus - Listed Wet No No No No No-Compliant - <82 CRI

Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="https://www.satco.com/">https://www.satco.com/</a>



