SATCO NUVO

Project Name

Location

Prepared By



Notes

O	
General	
Status	Active
Substitute	S13190
Watts	42W
Incandescent Equivalent	300W
Fluorescent Equivalent	85W
HID Equivalent	175W
Volts	120V-277V
Shape	ED28
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	6000L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	25000
Product Category	LED HID
Technology	LED
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
i uwei i aciui	0.0
Operating Position	Universal
Operating Position	Universal
Operating Position Operating Temperature	Universal
Operating Position Operating Temperature Physical	Universal -30C (-22F) to +65C (+149F)
Operating Position Operating Temperature Physical MOL	Universal -30C (-22F) to +65C (+149F) 8.54
Operating Position Operating Temperature Physical MOL MOD	Universal -30C (-22F) to +65C (+149F) 8.54 3.54
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White
Operating Position Operating Temperature Physical MOL MOD Lens Finish	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures.
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures.
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus Wet
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus Wet No
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus Wet No No
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus Wet No No Exempt - >2600 Lumens
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale California Status	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus Wet No No Exempt - >2600 Lumens Lawful for sale in California
Operating Position Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Additional Info Rated For Enclosed Fixture IP Rating Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star DLC Approved CA T20 / T24 Rationale	Universal -30C (-22F) to +65C (+149F) 8.54 3.54 White Glass White 0.49 HI-PRO Filament 120-277V Yes IP65 Not for use in vapor tight fixtures. 3 Year Limited - 12 hr per day CULus Wet No No Exempt - >2600 Lumens

Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



