

Project Name

Location

Prepared By



## SATCO S13151

72W/LED/HID-HB/850/120-277V/DI

### Notes

[www] 05-15-2024 04:42:54

### General

Status	Active
Watts	72W
Incandescent Equivalent	400W
Fluorescent Equivalent	100W
HID Equivalent	320W
Volts	120V-277V
Shape	HB51
Base	Mogul Extended
ANSI Base	EX39
Finish	White
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	82
Lumens	11000L
Beam Spread	180
Hours Rated	50000
Product Category	Hi-Bay Flood
Technology	LED
Min Compartment Size	Diameter: 11.81 in. Height: 13.78 in.
Ballasting Requirements	Ballast Bypass

### Electrical

Operating Frequency	50/60Hz
Dimming Type	Reverse Phase
Power Factor	0.9
Operating Position	Base Up
Surge Protection	Built-in surge protection - 6KV
THD	20%
Operating Temperature	-40C (-40F) to +60C (+140F)

### Physical

MOL	8.15
MOD	6.34
Lens Finish	Clear
Lens Material	Glass
Housing Color	White
Weight (lb.)	2.09

### Additional Information

Rated For Enclosed Fixture	Yes
IP Rating	IP40
Installation Notes	Not for use in vapor tight fixtures. Vertical Only with base up
Warranty	5 Year Limited - Hi-Pro

### Compliance

Safety Listing	cULus - Listed
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	P1BJY0BF
CA T20 / T24 Rationale	Exempt - Base Not Regulated

California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc.  
All Rights Reserved

For More Information Visit:  
<https://www.satco.com/>

