SATCO NUVO

Project Name

Location

Prepared By



Notes

3 04 45 0004 00 4

General	
Status	Active
Watts	45W/22W
Incandescent Equivalent	300W
Fluorescent Equivalent	100W
HID Equivalent	150W-175W
Volts	100V-277V
Shape	AP32
Base	Medium
ANSI Base	E26
Finish	White
CCT (Kelvin)	3000K/4000K/5000K
Temperature	Warm to Cool White
CRI	80
Lumens	5850L/3060L
Beam Spread	280
Dimmable	Yes-Dimmable
Hours Rated	50000
Lamp Type	Туре А
Technology	LED
Min Compartment Size	Length: 6 in. Width: 6 in. Height: 8.5 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50/60Hz
Dimming Type	Reverse Phase
Dimming Note	Only dimmable through wattage selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls.
Dimming Note Power Factor	selection switch on lamp. NOT dimmable with wall dimmers or any
	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls.
Power Factor	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls.
Power Factor Operating Position	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal
Power Factor Operating Position Surge Protection	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV
Power Factor Operating Position Surge Protection Operating Temperature	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV
Power Factor Operating Position Surge Protection Operating Temperature Physical	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC)
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White 1.69
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White 1.69
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White 1.69 Yes IP64 Lumen/Watt/CCT Ratio Chart in
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Note	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White 1.69 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents.
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Note Warranty Compliance	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White 1.69 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents.
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Note Warranty Compliance Safety Listing	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White 1.69 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents. 5 Year Limited - Hi-Pro
Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture IP Rating Specification Note Warranty Compliance	selection switch on lamp. NOT dimmable with wall dimmers or any other dimming controls. >0.9 Universal Built-in surge protection - 3KV -22C (-30F) to +45C (+113F) 7.05 3.9 Frost Polycarbonate (PC) White 1.69 Yes IP64 Lumen/Watt/CCT Ratio Chart in Documents. 5 Year Limited - Hi-Pro

DLC Approved	No
CA T20 / T24 Rationale	Exempt - >2600 Lumens
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



