

Project Name

Prepared By



**SATCO S18400** 

4.5W/LED/CFL/827/G23/BP

Notes

General	
Status	Active
Watts	4.5W
Fluorescent Equivalent	5W/7W/9W
Volts	120V-277V
Ballast Type	Туре В
Shape	PL
Base	G23 (2-Pin)
ANSI Base	G23
Finish	Frost
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	80+
Lumens	450L
Beam Spread	360
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Universal
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
On avating Tanan avature	250 ( 125) +- + 450 ( + 1125)

Electrical	
Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	-25C (-13F) to +45C (+113F)

Physical	
MOL	6.54
MOD	1.28
Housing Color	White
Weight (lb.)	0.1

Additional Information	
Rated For Enclosed Fixture	Yes
Warranty	5 Years

Compliance	
Safety Listing	cETLus - Classified
Location Rating	Damp
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED Lamp