SATCO NUVO

Project Name

Location Prepared By



Notes

[www] 05-15-2024 04:42:5

General	
Status	Active
Watts	5.5W
Incandescent Equivalent	40W
Volts	120V
Shape	T10
Base	Medium
ANSI Base	E26
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	90
Lumens	450L
Beam Spread	320
Dimmable	Yes-Dimmable
Dimming Note	120V only
Hours Rated	15000
Product Category	Tubular
Technology	LED
Electrical	
Operating Frequency	60Hz
Operating ricquerity	00112
Power Factor	0.75
Power Factor Operating Temperature	0.75
Power Factor	0.75
Power Factor Operating Temperature	0.75
Power Factor Operating Temperature Physical	0.75 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL	0.75 -20C (-4F) to +45C (+113F)
Power Factor Operating Temperature Physical MOL MOD	0.75 -20C (-4F) to +45C (+113F) 5 1.25
Power Factor Operating Temperature Physical MOL MOD Weight (lb.)	0.75 -20C (-4F) to +45C (+113F) 5 1.25
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062 Yes Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062 Yes Not for use in vapor tight fixtures.
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062 Yes Not for use in vapor tight fixtures. 3 Year Limited
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance Safety Listing	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062 Yes Not for use in vapor tight fixtures. 3 Year Limited cETLus - Listed
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance Safety Listing Location Rating	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062 Yes Not for use in vapor tight fixtures. 3 Year Limited cETLus - Listed Wet
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062 Yes Not for use in vapor tight fixtures. 3 Year Limited cETLus - Listed Wet No
Power Factor Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Installation Notes Warranty Compliance Safety Listing Location Rating Energy Star UL Application	0.75 -20C (-4F) to +45C (+113F) 5 1.25 0.062 Yes Not for use in vapor tight fixtures. 3 Year Limited cETLus - Listed Wet No Filament LED Lamp

Title 20 / 24 Status

RoHS Compliant

SDS Sheet

Lawful for sale

LED_Lamp

Yes

