## SATCO" NUVO"

Project Name

Location

Prepared By



## SATCO S23112

80W/LED/HID-HB/4K/120-277V

Notes

www] 05-15-2024 04:42:55

General	
Status	Active
Substitute	
Watts	80W
Incandescent Equivalent	400W
HID Equivalent	250W
Volts	120V-277V
Shape	
Base	Mogul Extended
ANSI Base	EX39
Finish	Translucent White
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	10000L
Beam Spread	115
Dimmable	Yes-Dimmable
Hours Rated	35000
Product Category	Hi-Bay
Technology	LED
Min Compartment Size	Length: 13.5 in. Width: 13.5 in. Height: 12 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	50-60Hz
Candlepower	3000
	Step Dimming
Dimming Type	otep Dimining
Dimming Note	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch
	Dimmable only via the built-in dimmer on the lamp. Not dimmable
Dimming Note	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch
Dimming Note Power Factor	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92
Dimming Note Power Factor Operating Position	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal
Dimming Note Power Factor Operating Position Surge Protection	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F)
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.)	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White 1.76
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White 1.76 Yes Fixture has a built-in dimming control feature
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Installation Notes	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White 1.76 Yes Fixture has a built-in dimming
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Installation Notes Warranty	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White 1.76 Yes Fixture has a built-in dimming control feature Not for use in vapor tight fixtures.
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Installation Notes	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White 1.76 Yes Fixture has a built-in dimming control feature Not for use in vapor tight fixtures.
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Installation Notes Warranty Compliance Safety Listing	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White 1.76 Yes Fixture has a built-in dimming control feature Not for use in vapor tight fixtures. 3 Year Limited cULus - Classified; cULus - Certified
Dimming Note Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Material Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Specification Note Installation Notes Warranty Compliance	Dimmable only via the built-in dimmer on the lamp. Not dimmable via wall switch 0.98/0.92 Universal Built-in surge protection - 6KV -40C (-40F) to +60C (+140F) 10.12 7.48 Plastic White 1.76 Yes Fixture has a built-in dimming control feature Not for use in vapor tight fixtures. 3 Year Limited cULus - Classified; cULus -

DLC Approved	No
CA T20 / T24 Rationale	T20 Exempt - Not A Regulated Product
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <u>https://www.satco.com/</u>

