

Project Name

Location

Prepared By



SATCO S28690

13T5/LED/46-835/BP/HE/SE-DE

Notes

(www) 04-13-2023 00:25:10

General

| | |
|-------------------------|------------------|
| Status | Active |
| Watts | 13W |
| Incandescent Equivalent | 50W |
| Fluorescent Equivalent | 28W |
| Volts | 120V-277V |
| Ballast Type | Type B |
| Shape | T5 |
| Base | Miniature Bi Pin |
| ANSI Base | G5 |
| Nominal Length | 48 |
| Finish | Frost |
| CCT (Kelvin) | 3500K |
| Temperature | Neutral White |
| CRI | 80+ |
| Lumens | 1600L |
| Beam Spread | 240 |
| Hours Rated | 50000 |
| Product Category | Linear |
| Technology | LED |

Electrical

| | |
|-------------------------|-----------------------------|
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60Hz |
| Power Factor | 0.9 |
| THD | 20% |
| Operating Temperature | -25C (-13F) to +45C (+113F) |

Physical

| | |
|---------------|-------|
| MOL | 46 |
| MOD | 0.83 |
| Material | Glass |
| Lens Finish | Frost |
| Lens Material | Glass |
| Housing Color | White |
| Weight (lb.) | 0.37 |

Additional Information

| | |
|----------------------------|--|
| Shatter-Proof Type | PET Coated |
| Installation Notes | Not for use in vapor tight fixtures. |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5 Year Limited - T5 LED Bulbs - Ballast Bypass |

Compliance

| | |
|----------------------|--|
| Safety Listing | cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component |
| Location Rating | Damp |
| DLC Approved | Yes |
| DLC ID | PLYHW51UWNHJ |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| Colorado Status | Lawful for sale |
| Hawaii Status | Lawful for sale |
| Nevada Status | Lawful for sale |
| Vermont Status | Lawful for sale |
| Washington Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |