SATCO NUVO

Project Name

ocation Prepared By



Notes

rw1 10-21-2025 23:30:5

General	
Status	Discontinued
Substitute	S21299
Watts	4W
Incandescent Equivalent	40W
Volts	120V
Shape	CA11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80+
Lumens	350L
Beam Spread	360
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Floring	
Electrical	
Operating Frequency	60Hz
	60Hz 0.9
Operating Frequency	
Operating Frequency Power Factor	0.9
Operating Frequency Power Factor Operating Position Operating Temperature	0.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F) 4.69
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 4.69
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (Ib.) Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years cULus Damp
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years cULus Damp Non-Compliant
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale Lawful for sale Lawful for sale Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status Vermont Status	0.9 Universal -20C (-4F) to +45C (+113F) 4.69 1.38 0.03 Yes 2-Years CULus Damp Non-Compliant Non-Compliant Lawful for sale

LED_Lamp

SDS Sheet