## SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	4.5W
Incandescent Equivalent	40W
Volts	120V
Shape	B11
Base	Candelabra
ANSI Base	E12
Finish	Clear
CCT (Kelvin)	2700K
Temperature	Warm White
CRI	90+
Lumens	350L
Beam Spread	300
Dimmable	Yes-Dimmable
Hours Rated	15000
Product Category	Candle
Technology	LED
Smart Product Info	
IOT Enabled	No
Integrated Camera	No
Electrical	
Operating Frequency	60Hz
	60Hz 0.9
Operating Frequency	
Operating Frequency Power Factor	0.9
Operating Frequency Power Factor Operating Position	0.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature	0.9 Universal
Operating Frequency Power Factor Operating Position Operating Temperature Physical	0.9 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL	0.9 Universal -20C (-4F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD	0.9 Universal -20C (-4F) to +45C (+113F) 3.75 1.25
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color	0.9 Universal -20C (-4F) to +45C (+113F) 3.75 1.25 None
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD  Housing Color  Weight (lb.)  Additional Information	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.)	0.9 Universal -20C (-4F) to +45C (+113F) 3.75 1.25 None
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03 Yes
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty Compliance	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years
Operating Frequency Power Factor Operating Position Operating Temperature Physical MOL MOD Housing Color Weight (lb.) Additional Information Rated For Enclosed Fixture Warranty	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03 Yes
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years  cULus - Certified; cULus - Listed
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years  cULus - Certified; cULus - Listed Damp
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years  CULus - Certified; cULus - Listed Damp Lawful for sale in California
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status Title 20 / 24 Status	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years  CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years  CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years  CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed Lawful for sale Lawful for sale
Operating Frequency Power Factor Operating Position Operating Temperature  Physical  MOL  MOD Housing Color Weight (lb.)  Additional Information Rated For Enclosed Fixture Warranty  Compliance Safety Listing Location Rating California Status Title 20 / 24 Status Colorado Status Hawaii Status Nevada Status	0.9 Universal -20C (-4F) to +45C (+113F)  3.75 1.25 None 0.03  Yes 2-Years  CULus - Certified; cULus - Listed Damp Lawful for sale in California California T24 Listed Lawful for sale Lawful for sale Lawful for sale Lawful for sale

