SATCO' NUVO

Project Name

Location

Prepared By



SATCO S29917

40T8/LED/96-835/BP/FA8

Notes

General Status Active Watts 40W 125W Incandescent Equivalent Fluorescent Equivalent 59W Volts 120V-277V Ballast Type Туре В Shape Τ8 Base Single Pin ANSI Base Fa8 Nominal Length 96 White Finish CCT (Kelvin) 3500K Temperature Neutral White CRI 82 5300L Lumens Beam Spread 210 Hours Rated 50000 **Product Category** Linear LED Technology Electrical **Ballasting Requirements Ballast Bypass Operating Frequency** 50/60Hz Power Factor 0.9 THD 20% **Operating Temperature** -20C (-4F) to +45C (+113F) Physical MOL 94 MOD 1 Material Glass Lens Finish White 0.88 Weight (lb.) Additional Information Suitable for Emergency Lighting Additional Info only with Satco EM Driver #S8002 Shatter-Proof Type PET Coated Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes 5 Year Limited - T8 LED Bulbs -Warranty **Ballast Bypass** Compliance cULus - Classified; cULus -Safety Listing Certified; cRUus - Recognized Component Location Rating Damp Energy Star No **DLC Approved** Yes DLC ID PLSDLWQ3P1GE CA T20 / T24 Rationale Exempt - Base Not Regulated California Status Lawful for sale in California

| Title 20 / 24 Status | Lawful for sale |
|----------------------|-----------------|
| Colorado Status | Lawful for sale |
| Hawaii Status | Lawful for sale |
| Nevada Status | Lawful for sale |
| Vermont Status | Lawful for sale |
| Washington Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |

Copyright 2023 Satco Products, Inc. All Rights Reserved For More Information Visit: <u>https://www.satco.com/</u>

