## SATCO' NUVO

Project Name

Location

Prepared By



## SATCO S29919

40T8/LED/96-850/BP/FA8

Notes

General Status Active Watts 40W 125W Incandescent Equivalent Fluorescent Equivalent 59W Volts 120V-277V Ballast Type Туре В Shape Τ8 Base Single Pin ANSI Base Fa8 Nominal Length 96 White Finish CCT (Kelvin) 5000K Temperature Natural Light CRI 82 5500L Lumens Beam Spread 210 Hours Rated 50000 **Product Category** Linear LED Technology Electrical **Ballasting Requirements Ballast Bypass Operating Frequency** 50/60Hz Power Factor 0.9 THD 20% **Operating Temperature** -20C (-4F) to +45C (+113F) Physical MOL 94 MOD 1 Material Glass Lens Finish White 0.88 Weight (lb.) Additional Information Suitable for Emergency Lighting Additional Info only with Satco EM Driver #S8002 Shatter-Proof Type PET Coated Installation Notes Not for use in vapor tight fixtures. Rated For Enclosed Fixture Yes 5 Year Limited - T8 LED Bulbs -Warranty **Ballast Bypass** Compliance cULus - Classified; cULus -Safety Listing Certified; cRUus - Recognized Component Location Rating Damp Energy Star No **DLC Approved** Yes DLC ID PLZR8CUD8VL7 CA T20 / T24 Rationale Exempt - Base Not Regulated California Status Lawful for sale in California

Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale
Washington Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
NSF Approved	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved For More Information Visit: <u>https://www.satco.com/</u>

