



Notes

v] 10-21-2025 23:30

| General | |
|-------------------------|----------------------------|
| Status | Discontinued |
| Substitute | S39926 |
| Watts | 12W |
| Incandescent Equivalent | 60W |
| Fluorescent Equivalent | 25W |
| Volts | 120V-277V |
| Ballast Type | Туре В |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 36 |
| Finish | Frost |
| CCT (Kelvin) | 3000K |
| Temperature | Warm White |
| CRI | 80+ |
| Lumens | 1400L |
| Beam Spread | 210 |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Product Category | Linear |
| Technology | LED |
| Electrical | |
| Ballasting Requirements | Ballast Bypass |
| Power Factor | 0.9 |
| Operating Temperature | -20C (-4F) to +45C (+113F) |
| Physical | |
| MOL | 36 |
| MOD | 1 |
| Manage at a 1 | Class |

| Physical | |
|------------------------|-------|
| MOL | 36 |
| MOD | 1 |
| Material | Glass |
| Lens Finish | Frost |
| Lens Material | Glass |
| Additional Information | |

| Additional Information | |
|----------------------------|---|
| Tube Guard Use | Yes |
| Installation Notes | Not for use in vapor tight fixtures. Existing wiring to both sockets can remain in place. Will work on both shunted or non-shunted sockets. |
| Specification Note | Built-in shock resistant circuit - (not hot until both ends are installed) |
| Rated For Enclosed Fixture | Yes |
| Warranty | 5-Years |

| Compliance | |
|----------------------|---------------------------------------|
| Safety Listing | cULus - Classified; cULus - Certified |
| Location Rating | Damp |
| DLC Approved | No |
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| Colorado Status | Lawful for sale |
| Hawaii Status | Lawful for sale |
| Nevada Status | Lawful for sale |
| Vermont Status | Lawful for sale |
| Washington Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |