

Project Name

Location

Prepared By



**Notes**

[www] 11-06-2021 02:55:03

**General**

Status	Transitioning
Substitute	S49934
Watts	12W
Fluorescent Equivalent	25W-32W
Ballast Type	Type A
Shape	T8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
Finish	Gloss
CCT (Kelvin)	3000
Temperature	Warm White
CRI	82
Lumens	1700L
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED

**Electrical**

Ballasting Requirements	Ballast required. Direct Replacement-for use on Instant Start and Rapid Start ballasts with no rewiring required. May not be compatible with every ballast. Refer to the ballast compatibility chart
Power Factor	0.9
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

**Physical**

MOL	48
MOD	1
Lens Finish	Gloss

**Additional Information**

Warranty	5 Year Limited - T8 LED Bulbs
----------	-------------------------------

**Compliance**

Safety Listing	cULus
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PL6UOQKEXHCD
California Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes