

Project Name

Location Prepared By



Notes

3 05 15 0001 01 10

| General | |
|--|---|
| Status | Active |
| Watts | 12W |
| Incandescent Equivalent | 50W |
| Fluorescent Equivalent | 25W |
| Volts | 120V-277V |
| Ballast Type | Туре В |
| Shape | T8 |
| Base | Medium Bi Pin |
| ANSI Base | G13 |
| Nominal Length | 36 |
| Finish | Gloss White |
| CCT (Kelvin) | 3500K |
| Temperature | Neutral White |
| CRI | 82 |
| Lumens | 1400L |
| Beam Spread | 210 |
| Hours Rated | 50000 |
| Product Category | T8 |
| Technology | LED |
| Electrical | |
| | Dallant Divinana |
| Ballasting Requirements | Ballast Bypass |
| Operating Frequency | 50/60Hz |
| Power Factor | 0.9 |
| Operating Temperature | 20% 20C (4E) to +45C (+112E) |
| Operating Temperature | -20C (-4F) to +45C (+113F) |
| Physical | |
| MOL | 35.78 |
| MOD | 1.1 |
| Material | Glass |
| | |
| Lens Finish | Gloss White |
| Lens Finish Lens Material | Gloss White Glass |
| | |
| Lens Material | Glass |
| Lens Material Housing Color Weight (lb.) | Glass White |
| Lens Material Housing Color | Glass White 0.33 |
| Lens Material Housing Color Weight (lb.) | Glass White |
| Lens Material Housing Color Weight (lb.) Additional Information | Glass White 0.33 Equivalent CCT selectable option |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info | Glass White 0.33 Equivalent CCT selectable option available in S11765 |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty Compliance Safety Listing | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass cULus - Classified; cRUus - Recognized Component |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty Compliance Safety Listing Location Rating | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - Recognized Component Damp |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty Compliance Safety Listing Location Rating Energy Star | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - Recognized Component Damp No |
| Lens Material Housing Color Weight (lb.) Additional Information Additional Info Tube Guard Use Installation Notes Specification Note Warranty Compliance Safety Listing Location Rating | Glass White 0.33 Equivalent CCT selectable option available in S11765 Approved for use with tube guards Not for use in vapor tight fixtures. Built-in shock resistant circuit - (not hot until both ends are installed) 5 Year Limited - T8 LED Bulbs - Ballast Bypass CULus - Classified; cRUus - Recognized Component Damp |

| CA T20 / T24 Rationale | Exempt - Base Not Regulated |
|------------------------|-------------------------------|
| California Status | Lawful for sale in California |
| Title 20 / 24 Status | Lawful for sale |
| Colorado Status | Lawful for sale |
| Hawaii Status | Lawful for sale |
| Nevada Status | Lawful for sale |
| Vermont Status | Lawful for sale |
| Washington Status | Lawful for sale |
| RoHS Compliant | Yes |
| FCC Compliant | Yes |
| NSF Approved | Yes |
| SDS Sheet | LED_Lamp |

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: https://www.satco.com/



