

Project Name

Location

Prepared By



SATCO S9953

15PLL/LED/840/BP

Notes

[www] 05-15-2024 04:42:59

General

Status	Active
Substitute	S18422
Watts	15W
Fluorescent Equivalent	36W
Volts	120V-277V
Ballast Type	Type B
Shape	T5
Base	2G11
ANSI Base	2G11
Finish	Frost
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80
Lumens	2000L
Beam Spread	270
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	PL
Operating Position	Universal
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass
Operating Frequency	50/60Hz
Power Factor	0.9
THD	20% (+/-5%)
Operating Temperature	-20C (-4F) to +45C (+113F)

Physical

MOL	16.5
MOD	0.68
Housing Color	White
Weight (lb.)	0.36

Additional Information

Installation Notes	Not for use in vapor tight fixtures.
Rated For Enclosed Fixture	Yes
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus
Location Rating	Damp
Energy Star	No
DLC Approved	No
NSF Approved	Yes
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Vermont Status	Lawful for sale

Washington Status	Lawful for sale
RoHS Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc.
All Rights Reserved

For More Information Visit:
<https://www.satco.com/>

