## SATCO NUVO

Project Name

Location

Prepared By



## Notes

54W/LED/HID/5K/100-277V/EX39

www] 01-15-2024 02:40:1

General	
	D:
Status	Discontinued
Substitute	S49394
Watts	54W
Incandescent Equivalent	300W
Fluorescent Equivalent	85W
HID Equivalent	250W
Volts	100V-277V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000K
Temperature	Natural Light
CRI	80
Lumens	7722L
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 15.75 in. Width: 8 in.  Depth: 8 in.
Ballasting Requirements	Ballast Bypass- Direct wire only 100V-277V
Electrical	
Working Voltage	AC 100-277V
Working Voltage Operating Frequency	AC 100-277V 50/60Hz
Operating Frequency	50/60Hz
Operating Frequency Power Factor	50/60Hz >0.9
Operating Frequency Power Factor Operating Position	50/60Hz >0.9 Base Up or Down
Operating Frequency Power Factor Operating Position Surge Protection	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical	50/60Hz >0.9 Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34 Clear
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34  Clear  Plastic (PS)
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34  Clear  Plastic (PS)  White
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34  Clear  Plastic (PS)  White
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.) Additional Information	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34  Clear  Plastic (PS)  White 1.89  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34  Clear  Plastic (PS)  White 1.89  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info	50/60Hz >0.9  Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34 Clear Plastic (PS) White 1.89  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34  Clear  Plastic (PS)  White 1.89  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas  Yes  IP64  DLC 5.1 replacement S23142;
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating Specification Note	50/60Hz >0.9  Base Up or Down  Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34  Clear  Plastic (PS)  White  1.89  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas  Yes  IP64  DLC 5.1 replacement S23142; Non-DLC replacement S49394
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL  MOD  Lens Finish  Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating  Specification Note  Shatter-Proof Type	50/60Hz >0.9  Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34 Clear Plastic (PS) White 1.89  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23142; Non-DLC replacement S49394 Shatter resistant materials
Operating Frequency Power Factor Operating Position Surge Protection Operating Temperature  Physical  MOL MOD Lens Finish Lens Material Housing Color Weight (lb.)  Additional Information  Additional Info  Rated For Enclosed Fixture IP Rating Specification Note Shatter-Proof Type Warranty	50/60Hz >0.9  Base Up or Down Built-in surge protection - 4KV -25C (-13F) to +45C (+113F)  9.03 3.34 Clear Plastic (PS) White 1.89  Emits no UV light; Contains no Mercury (Hg); Acceptable for use in food prep areas Yes IP64 DLC 5.1 replacement S23142; Non-DLC replacement S49394 Shatter resistant materials

Location Rating	Damp
Energy Star	No
DLC Approved	No
CA T20 / T24 Rationale	Exempt - Base Not Regulated
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
Colorado Status	Lawful for sale
Hawaii Status	Lawful for sale
Nevada Status	Lawful for sale
Washington Status	Lawful for sale
Vermont Status	Lawful for sale
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Copyright 2023 Satco Products, Inc. All Rights Reserved

For More Information Visit: <a href="https://www.satco.com/">https://www.satco.com/</a>



