## SATCO NUVO

General

Project Name

Location

on

Prepared By



## **NUVO TH413**

12W LED TRACK HEAD PINCH BACK

## Notes

TypeTrack HeadWattage12WFinishWhiteBeam Angle36CCT (kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsCRIUmen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimmableLength (in.)2.88Length (in.)3.63Extension (in.)5.5CorplianceSafety ListingSafety ListingCETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLeadRotS CompliantYesCanadian Standard ICES-005Class BSo SheetLED_Fixture	Status	Active
FinishWhiteBeam Angle36CCT (kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsCRI90+4Lumen Output1020LRated HoursRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceJoryUL ApplicationTrackENREGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesCanadian Standard ICES-005Class BSD SheetLED_Fixture	Туре	Track Head
Beam Angle36CCT (Kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecifications90+CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05Dimensions2.88Height (in.)2.88Udth (in.)2.88Safety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENRGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Standard ICES-005Class BSD SheetLED_Fixture	Wattage	12W
CCT (Kelvin)3000KTemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsIndoorCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05Dimensions	Finish	White
TemperatureWarm WhiteBaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsIndoorCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Standard ICES-005Class BSD SheetLED_Fixture	Beam Angle	36
BaseIntegratedANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsIndoorCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05Dimensions2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia StatusLeadRohS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSD SheetLED_Fixture	CCT (Kelvin)	3000K
ANSI BaseIntegratedIndoor or Outdoor FixtureIndoorSpecificationsCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Length (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENRRGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Standard ICES-005Class BSDS SheetHeadLocation Standard ICES-005Class BSolowerSolower	Temperature	Warm White
Indoor or Outdoor FixtureIndoorSpecificationsIndoorCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Length (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCanpliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesSolos BestLED_Fixture	Base	Integrated
SpecificationsCRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Length (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCanpliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC CompliantYesFCC StheetLED_Fixture	ANSI Base	Integrated
CRI90+Lumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceJurySafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedCalifornia T24 ListedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCanadian Standard ICES-005Class BSDS SheetLD_Fixture	Indoor or Outdoor Fixture	Indoor
InternationalDefensionalLumen Output1020LRated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Specifications	
Rated Hours30000Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_Fixture	CRI	90+
Voltage120VDimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_Fixture	Lumen Output	1020L
DimmableYes-DimmableDimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCompliantYesFCC CompliantYesFCC CompliantYesSo SheetLED_Fixture	Rated Hours	30000
Dimming Note120V onlyWeight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_Fixture	Voltage	120V
Weight (lb.)1.05DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_Fixture	Dimmable	Yes-Dimmable
DimensionsHeight (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesSDS SheetLED_Fixture	Dimming Note	120V only
Height (in.)2.88Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Weight (lb.)	1.05
Width (in.)2.88Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Dimensions	
Length (in.)3.63Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesSDS SheetLED_Fixture	Height (in.)	2.88
Extension (in.)5.5ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Width (in.)	2.88
ComplianceSafety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Length (in.)	3.63
Safety ListingcETLus - ListedLocation RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Extension (in.)	5.5
Location RatingDryUL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Compliance	
UL ApplicationTrackENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Safety Listing	cETLus - Listed
ENERGY STARNoDLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Location Rating	Dry
DLC ApprovedNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	UL Application	Track
California StatusLawful for sale in CaliforniaTitle 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	ENERGY STAR	No
Title 20 / 24 StatusCalifornia T24 ListedCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	DLC Approved	No
California Prop 65LeadRoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	California Status	Lawful for sale in California
RoHS CompliantYesFCC CompliantYesCanadian Standard ICES-005Class BSDS SheetLED_Fixture	Title 20 / 24 Status	California T24 Listed
FCC Compliant Yes   Canadian Standard ICES-005 Class B   SDS Sheet LED_Fixture	California Prop 65	Lead
Canadian Standard ICES-005 Class B   SDS Sheet LED_Fixture	RoHS Compliant	Yes
SDS Sheet LED_Fixture	FCC Compliant	Yes
	Canadian Standard ICES-005	Class B
Additional Information	SDS Sheet	LED_Fixture
	Additional Information	

Warranty

3-Years

