## SATCO NUVO

Project Name

```
Location Prepared By
```



## NUVO 60-5263

BEAKER 2 LT WALL SCONCE

Notes

StatusActiveCollectionBeakerFinishBrushed NickelStyleTransitionalNumber of Lamps2Height (in.)4.75Width (in.)23.75Extension (in.)5.88Indoor or Outdoor FixtureIndoorSpecificationsIncandescentBaseMediumBulb TypeIncandescentMax Wattage60WVoltage120VBulb IncludedYesDimmableLamp DependentDimming NoteGimmers are dependent on the light bubls(s) usedWeight (b.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceSafety ListingCUlusLocation RatingDampUL ApplicationWallExtersion (Status)Lawful for saleSafety ListingLawful for saleCorplianteNoADA CompliantNoCalifornia StatusLawful for saleCalifornia Prop 65LeadRoth 2 / 24 StatusLawf	General	
FinishBrushed NickelStyleTransitionalNumber of Lamps2Height (in.)4.75Width (in.)23.75Extension (in.)5.88Indoor or Outdoor FixtureIndoorSpecificationsIncandescentBaseMediumBuib TypeIncandescentMax Wattage60WVoltage120VBuib IncludedYesDimming NoteLamp DependentDimming requirements and compatibledimmers are dependent on the light bulb(s)usedSa87Up/Down InstallationUniversalFixture TypeSconceFixture MaterialSteelDimensionsBack Plate or Canopy Diameter (in.)4.75Safety ListingCullusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia Frop 65LeadRoht StatusLawful for sale in CaliforniaTitle 20 / 24 stausLawful for sale in CaliforniaCalifornia Frop 65LeadRoHS CompliantYesAdditional InformationYesAdditional InformationYesAdditional InformationYesAdditional InformationYesAdditional InformationYesAdditional InformationYesIncludes(2) 20W Incandescent LampsInstalled vertically.Yes	Status	Active
StyleTransitionalNumber of Lamps2Height (in.)4.75Width (in.)23.75Extension (in.)5.88Indoor or Outdoor FixtureIndoorSpecificationsBaseMediumBulb TypeIncandescentMax Wattage60WVoltage120VBulb IncludedYesDimmableLamp DependentDimming NoteDimmers are dependent on the light bub(s) usedReplacement Bulb52415Glass DescriptionClearWeight (ib.)3.87Up/Down InstallationUniversalFixture MaterialSteelDimeater of the out of	Collection	Beaker
Number of Lamps2Height (in.)4.75Width (in.)23.75Extension (in.)5.88Indoor of Outdoor FixtureIndoorSpecificationsBaseBuib TypeIncandescentMax Wattage60WVoltage120VBuib IncludedYesDimmableLamp DependentDimming NoteDimming requirements and compatibleGlass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture TypeSconceFixture TypeSconceSafety ListingcULusLocan RatingDampUL ApplicationWallENERCY STARNoADANoACompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20/24 StatusLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia StatusLawful for sale in CaliforniaTitle 20/24 StatusLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaTitle 20/24 StatusLawful for sale in CaliforniaCalifornia StatusLawful for sale in CaliforniaTitle 20/24 StatusLawful for sale in CaliforniaCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationYesAdditional InformationYesIncludes(2) 20W Incandescent Lamp	Finish	Brushed Nickel
Height (in.)4.75Width (in.)23.75Extension (in.)5.88Indoor or Outdoor FixtureIndoorSpecifications	Style	Transitional
Width (in.)23.75Extension (in.)5.88Indoor or Outdoor FixtureIndoorSpecificationsIncandescentBaseMediumBulb TypeIncandescentMax Wattage60WVoltage120VBulb IncludedYesDimmableLamp DependentDimming Notedimmers are dependent on the light bulb(s) usedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture TypeSconceFixture MaterialSteelDimensions11.75ComplianceDampLu ApplicationWallENRGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia S	Number of Lamps	2
Extension (in.)5.88Indoor or Outdoor FixtureIndoorSpecificationsIncandescentBaseMediumBulb TypeIncandescentMax Wattage60WVoltage120VBulb IncludedYesDimmableLamp DependentDimming NoteDimming requirements and compatible dimmers are dependent on the light bub(s) usedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture MaterialSteelDimensionsEach Plate or Canopy Diameter (in.)4.7511.75ComplianceSafety ListingLocation RatingDampUL ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Torp 65LeadRoHS CompliantYesAdditional InformationYesIncludes(2) 20W Incandescent LampsInstallation Notesif installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Height (in.)	4.75
Indoor or Outdoor Fixture Indoor  Specifications Base Medium Bulb Type Incandescent Max Wattage 60W Voltage 120V Bulb Included Yes Dimmable Lamp Dependent Dimming Note Dimming requirements and compatible dimmers are dependent on the light bulb(s) used Replacement Bulb 52415 Glass Description Clear Weight (lb.) 3.87 Up/Down Installation Universal Fixture Type Sconce Fixture Material Steel Dimensions Back Plate or Canopy Diameter (in.) 4.75 Compliance Safety Listing CulLus Location Rating Damp UL Application Wall ENERGY STAR No DLC Approved No CAA Compliant No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Status Lawful for sale in California Title 20 / 24 Status (2) 20W Incandescent Lamps Includes (2) 20W Incandescent Lamps Includes (2) 20W Incandescent Lamps Installation Notes Installation Notes Installed vertically.	Width (in.)	23.75
SpecificationsBaseMediumBulb TypeIncandescentMax Wattage60WVoltage120VBulb IncludedYesDimmableLamp DependentDimming NoteDimming requirements and compatibledimmers are dependent on the light bulb(s) usedusedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture TypeSconceFixture TypeSconceSafety ListingCULusLocation RatingDampUL ApplicationWallENERY STARNoCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationYesIncludes(2) 20W Incandescent LampsIncludes(2) 20W Incandescent LampsInstalled vertically.Installed vertically.	Extension (in.)	5.88
Base Medium Bulb Type Incandescent Max Wattage 60W Voltage 120V Bulb Included Yes Dimmable Lamp Dependent Dimming Note Dimming requirements and compatible dimmers are dependent on the light bulb(s) used Replacement Bulb S2415 Glass Description Clear Weight (lb.) 3.87 Up/Down Installation Universal Fixture Type Sconce Fixture Material Steel Dimensions Back Plate or Canopy Diameter (in.) 4.75 Top to Outlet 11.75 Compliance Safety Listing CULus Location Rating Damp UL Application Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status California Frop 65 Editional Information Includes (2) 20W Incandescent Lamps Includes (2) 20W Incandescent Lamps Installation Notes Installation Notes Installed vertically.	Indoor or Outdoor Fixture	Indoor
Bulb TypeIncandescentMax Wattage60WVoltage120VBulb IncludedYesDimmableLamp DependentDimming NoteDimming requirements and compatible dimmers are dependent on the light bulb(s) usedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture TypeSteelDimensions11.75Back Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingLocation RatingDampUL ApplicationWallENRGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia InformationYesAdditional InformationYesIncludes(2) 20W Incandescent LampsIncludesIf installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Specifications	
Max Wattage60WVoltage120VBulb IncludedYesDimmableLamp DependentDimming NoteDimming requirements and compatible dimmers are dependent on the light bulb(s) usedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture TypeSconceDimensions11.75Back Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationYesIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Outlet is 2.25 inches when installed vertically.	Base	Medium
Voltage120VBulb IncludedYesDimmableLamp DependentDimming NoteDimming requirements and compatible dimmers are dependent on the light bulb(s) usedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture MaterialSteelDimensions11.75Back Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Bulb Type	Incandescent
BuilbYesDimmableLamp DependentDimming NoteDimming requirements and compatible dimmers are dependent on the light bulb(s) usedReplacement BulbS2415Glass DescriptionClearWeight (Ib.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture MaterialSteelDimensionsBack Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Max Wattage	60W
DimmableLamp DependentDimming NoteDimming requirements and compatible dimmers are dependent on the light bulb(s) usedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture MaterialSteelDimensionsSteelBack Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Voltage	120V
Dimming NoteDimming requirements and compatible dimmers are dependent on the light bulb(s) usedReplacement Bulb\$2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture MaterialSteelDimensionsSteelBack Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLeadNos California Trop 65LeadCalifornia Notes(2) 20W Incandescent LampsIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Bulb Included	Yes
Dimming Notedimmers are dependent on the light bulb(s) usedReplacement BulbS2415Glass DescriptionClearWeight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture MaterialSteelDimensionsBack Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional Information(2) 20W Incandescent LampsIncludes(2) 20W Incandescent LampsInstallation Notesif installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Dimmable	Lamp Dependent
ClearWeight (Ib.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture MaterialSteelDimensionsBack Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingLocation RatingDampUL ApplicationWallENRGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIf installed horizontally the Top to Outlet is 2.25Installation NotesIf installed horizontally the Top to Outlet is 2.15	Dimming Note	dimmers are dependent on the light bulb(s)
Weight (lb.)3.87Up/Down InstallationUniversalFixture TypeSconceFixture TypeSteelDimensions4.75Back Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDL ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional Informationfi installed horizontally the Top to Oulet is 2.25Installation NotesIf installed horizontally the Top to Oulet is 2.25	Replacement Bulb	S2415
Up/Down InstallationUniversalFixture TypeSconceFixture TypeSconceFixture MaterialSteelDimensions4.75Back Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIf installed horizontally the Top to Oulet is 2.25Installation NotesIf installed horizontally the Top to Oulet is 11.75 inches when installed vertically.	Glass Description	Clear
Fixture TypeSconceFixture MaterialSteelDimensionsBack Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesAdditional InformationIf installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Weight (lb.)	3.87
Fixture MaterialSteelDimensions4.75Back Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesAdditional InformationIf installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Up/Down Installation	Universal
DimensionsBack Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadROHS CompliantYesAdditional InformationIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Fixture Type	Sconce
Back Plate or Canopy Diameter (in.)4.75Top to Outlet11.75ComplianceCULusSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesAdditional Information(2) 20W Incandescent LampsIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Fixture Material	Steel
Top to Outlet11.75ComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIncludesIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Dimensions	
ComplianceSafety ListingcULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Oullet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Back Plate or Canopy Diameter (in.)	4.75
Safety ListingCULusLocation RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesAdditional InformationIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Oullet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Top to Outlet	11.75
Location RatingDampUL ApplicationWallENERGY STARNoDLC ApprovedNoADA CompliantNoCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesAdditional InformationIncludesIncludes(2) 20W Incandescent LampsInstallation NotesIf installed horizontally the Top to Outlet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Compliance	
UL Application     Wall       ENERGY STAR     No       DLC Approved     No       ADA Compliant     No       California Status     Lawful for sale in California       Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       RoHS Compliant     Yes       Additional Information     Includes       Includes     (2) 20W Incandescent Lamps       Installation Notes     If installed horizontally the Top to Oullet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Safety Listing	cULus
ENERGY STAR     No       DLC Approved     No       ADA Compliant     No       California Status     Lawful for sale in California       Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       RoHS Compliant     Yes       Additional Information     Includes       Includes     (2) 20W Incandescent Lamps       Installation Notes     If installed horizontally the Top to Oullet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Location Rating	Damp
DLC Approved     No       ADA Compliant     No       California Status     Lawful for sale in California       Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       RoHS Compliant     Yes       Additional Information     Includes       Includes     (2) 20W Incandescent Lamps       Installation Notes     If installed horizontally the Top to Oullet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	UL Application	Wall
ADA Compliant       No         California Status       Lawful for sale in California         Title 20 / 24 Status       Lawful for sale         California Prop 65       Lead         RoHS Compliant       Yes         Additional Information       Includes         Includes       (2) 20W Incandescent Lamps         Installation Notes       If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	ENERGY STAR	No
California Status       Lawful for sale in California         Title 20 / 24 Status       Lawful for sale         California Prop 65       Lead         RoHS Compliant       Yes         Additional Information       Includes         Includes       (2) 20W Incandescent Lamps         Installation Notes       If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	DLC Approved	No
Title 20 / 24 Status     Lawful for sale       California Prop 65     Lead       RoHS Compliant     Yes       Additional Information     Includes       Includes     (2) 20W Incandescent Lamps       Installation Notes     If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	ADA Compliant	No
California Prop 65     Lead       RoHS Compliant     Yes       Additional Information       Includes     (2) 20W Incandescent Lamps       Installation Notes     If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	California Status	Lawful for sale in California
RoHS Compliant     Yes       Additional Information     Includes       Includes     (2) 20W Incandescent Lamps       Installation Notes     If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Title 20 / 24 Status	Lawful for sale
Additional Information         Includes       (2) 20W Incandescent Lamps         Installation Notes       If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	California Prop 65	Lead
Includes       (2) 20W Incandescent Lamps         Installation Notes       If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	RoHS Compliant	Yes
Installation Notes         If installed horizontally the Top to Oulet is 2.25 inches. Top to Outlet is 11.75 inches when installed vertically.	Additional Information	
Installation Notes inches. Top to Outlet is 11.75 inches when installed vertically.	Includes	(2) 20W Incandescent Lamps
Warranty 1-Year	Installation Notes	inches. Top to Outlet is 11.75 inches when
	Warranty	1-Year