SATCO NUVO

IOT Enabled

Integrated Camera

Project Name

ocation Prepared By



NUVO 62-1703

BLINK 9W LED 5" RND BR. NICKEL

Notes

v] 08-18-2025 00:0

Status	Active
Fixture Type	Flush Mount
Finish	Brushed Nickel
Wattage	9W
Lumen Output	650L-680L
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Indoor or Outdoor Fixture	Indoor

No

No

Technology	LED
Color Temperature	Warm White to Natural Light
CRI	90+
Voltage	120V
Beam Angle	100
Rated Hours	50000
Operating Temperature	-20C (-4F) to +40C (+104F)
Dimmable	Yes-Dimmable
Dimming Note	120V only
Lens Material	Poly methyl methacrylate (PMMA)
Surge Protection	Built-in surge protection - 2.5KV
Weight (lb.)	0.59
Material	Die-Cast Aluminum

Dimensions	
Height (in.)	0.67
Width (in.)	5
Compliance	

Compliance	
Safety Listing	cETLus - Listed
Location Rating	Wet
ENERGY STAR	Yes
ES Unique ID	ESID-3553077
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
California Prop 65	Lead
RoHS Compliant	Yes
NEC Compliance	Clothes Closet Certified - Reg: 410.16 (A)(3) and 410.16 (C)(5)
FCC Compliant	Yes
Canadian Standard ICES-005	Class B
Flicker Free	No
SDS Sheet	LED_Fixture
	_

Additional Information	
Additional Information	UGR - 28.89; SDCM - 464; Hi pot - DC-1550V; Edge-lit - Yes
Specification Note	Overall height of fixture and driver: 1.59"
Installation Notes	Surface mount; Compatible with 3"&4" J-box and pancake J-box with additional accessory
Warranty	5-Years