SATCO' NUVO

Project Name

Prepared By



NUVO 62-1723

BLINK 13W LED 9" RND BR. NICK

Notes

Status Fixture Type Finish Wattage Lumen Output CCT (Kelvin) Indoor or Outdoor Fixture Smart Product Info IOT Enabled Integrated Camera	Active Flush Mount Brushed Nickel 13W 1200L-1250L 2700K/3000K/3500K/4000K/5000K Indoor
Finish Wattage Lumen Output CCT (Kelvin) Indoor or Outdoor Fixture Smart Product Info IOT Enabled Integrated Camera	Brushed Nickel 13W 1200L-1250L 2700K/3000K/3500K/4000K/5000K Indoor
Wattage Lumen Output CCT (Kelvin) Indoor or Outdoor Fixture Smart Product Info IOT Enabled Integrated Camera	13W 1200L-1250L 2700K/3000K/3500K/4000K/5000K Indoor
Lumen Output CCT (Kelvin) Indoor or Outdoor Fixture Smart Product Info IOT Enabled Integrated Camera	1200L-1250L 2700K/3000K/3500K/4000K/5000K Indoor
CCT (Kelvin) Indoor or Outdoor Fixture Smart Product Info IOT Enabled Integrated Camera	2700K/3000K/3500K/4000K/5000K Indoor
Indoor or Outdoor Fixture Smart Product Info IOT Enabled Integrated Camera	Indoor
Smart Product Info IOT Enabled Integrated Camera	
IOT Enabled Integrated Camera	No
Integrated Camera	No
-	
	No
Specifications	
	LED
Technology	
Color Temperature CRI	Warm White to Natural Light
Voltage	120V
Beam Angle	100
Rated Hours	50000 200 (45) to 1400 (11045)
Operating Temperature	-20C (-4F) to +40C (+104F)
Dimmable	Yes-Dimmable
Dimming Note	120V only
Lens Material	Poly methyl methacrylate (PMMA)
Surge Protection	Built-in surge protection - 2.5KV
Weight (lb.)	1.21
Material	Die-Cast Aluminum
Dimensions	
Height (in.)	0.67
Width (in.)	9
Compliance	
Safety Listing	cETLus - Listed
Location Rating	Wet
ENERGY STAR	Yes
ES Unique ID	ESID-3553089
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
	Lead
California Prop 65	Yes
RoHS Compliant FCC Compliant	Yes
	Class B
Canadian Standard ICES-005 Flicker Free	No
SDS Sheet	LED_Fixture
Additional Information	
Additional Information	UGR - 26.14; SDCM - 464; Hi pot - DC-1550V Edge-lit - Yes
Specification Note	Overall height of fixture and driver: 1.59"
Installation Notes	Surface mount; Compatible with 3"&4" J-box and pancake J-box with additional accessory

