## SATCO NUVO

Project Name

Prepared By

## NUVO 62-1820 7" LED DISK LIGHT W/ OCC WHITE

Notes

| Status                     | Active  |
|----------------------------|---|
| Substitute                 | 62-1820R1   |
| Finish                     | White   |
| Wattage                    | 16W   |
| Style                      | Contemporary  |
| CCT (Kelvin)               | 2700K/3000K/3500K/4000K/5000K   |
| Color Temperature          | Warm White to Natural Light   |
| Width (in.)                | 7.06  |
| Height (in.)               | 1.42  |
| Indoor or Outdoor Fixture  | Indoor  |
| Smart Product Info         |   |
| IOT Enabled                | No  |
| Integrated Camera          | No  |
| Specifications             |   |
| Technology                 | LED   |
| CRI                        | 93+   |
| Lumen Output               | 900L-1000L  |
| Rated Hours                | 50000   |
| Voltage                    | 120V  |
| Dimmable                   | Yes-Dimmable  |
| Dimming Note               | Bi-Level Dimmable   |
| Photocell or Sensor        | Has Occupancy Sensor  |
| Weight (lb.)               | 0.61  |
| Sloped Ceiling             | Yes   |
| Fixture Shape              | Round   |
| Fixture Material           | Steel   |
| Fixture Type               | Disk Light  |
| Operating Temperature      | -25C (-13F) to +40C (+104F)   |
| Compliance                 |   |
| Safety Listing             | cETLus  |
| Location Rating            | Damp  |
| ENERGY STAR                | No  |
| DLC Approved               | No  |
| NSF Approved               | No  |
| California Status          | Lawful for sale in California   |
| Title 20 / 24 Status       | California T24 Listed   |
| California Prop 65         | Lead  |
| RoHS Compliant             | Yes   |
| FCC Compliant              | Yes   |
| Canadian Standard ICES-005 | Class B   |
| SDS Sheet                  | LED_Fixture   |
| Additional Information     | _   |
|                            | PIR sensor specs: Detection area up to 20<br>max; Bi-level 30-100% or 0-100% with a |
| Additional Information     | minimum shut-off time of 0-3 sec to a maximum of 5 minutes.                         |
| Installation Notes         | Keyhole Slots   |
|                            | 5-Years   |

