SATCO NUVO

IOT Enabled

Dimensions

Width (in.) Length (in.)

Project Name

Location Prepared By



Notes

10-27-2025 05:2

Status	Active
Fixture Type	Ceiling Wrap
Finish	White
Wattage	14W
Lumen Output	1298L-1391L
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Indoor or Outdoor Fixture	Indoor

No

Integrated Camera	No	
Specifications		
Technology	LED	
Color Temperature	Warm White to Natural Light	
CRI	90+	
Voltage	120V	
Beam Angle	110	
Rated Hours	50000	
Operating Temperature	-20C (-4F) to +40C (+104F)	
Dimmable	Non-Dimmable	
Lens Material	Polycarbonate (PC)	
Surge Protection	Built-in surge protection - 2KV	
Weight (lb.)	2.35	
Material	Steel	

Extension (in.)	2.51	
Compliance		
Safety Listing	cETLus	
Location Rating	Damp	
California Status	Lawful for sale in California	
Title 20 / 24 Status	Lawful for sale	
California Prop 65	Lead	
RoHS Compliant	Yes	
FCC Compliant	Yes	
Canadian Standard ICES-005	Class B	
SDS Sheet	LED_Fixture	

4.4

18

Additional Information	Tamper Resistant Dual GFCI Outlet with 15 amp circuit with 14 gauge wire; 0.025 second GFCI Trip Time; The outlet is front facing, It has an easy to read diagnostic indicator; Built in protection against shock; Most used application for this product would be a bathroom vanity
Installation Notes	Standard 3-inch and 4-inch Keyhole Slots
Warranty	5-Years