SATCO NUVO

IOT Enabled

Width (in.)

Length (in.) Extension (in.)

Project Name

Location Prepared By



Notes

08-25-2025 01:2

Status	Active
Fixture Type	Ceiling Wrap
Finish	White
Wattage	14W
Lumen Output	1298L-1391L
CCT (Kelvin)	2700K/3000K/3500K/4000K/5000K
Indoor or Outdoor Fixture	Indoor

No

Integrated Camera	No
Specifications	
Technology	LED
Color Temperature	Warm White to Natural Light
CRI	90+
Voltage	120V
Beam Angle	110
Rated Hours	50000
Operating Temperature	-20C (-4F) to +40C (+104F)
Dimmable	Non-Dimmable
Lens Material	Polycarbonate (PC)
Surge Protection	Built-in surge protection - 2KV
Weight (lb.)	2.35
Material	Steel

Safety Listing	cETLus
Location Rating	Damp
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class B
SDS Sheet	LED Fixture

4.4

18

2.51

Additional Information	Tamper Resistant Dual GFCI Outlet with 15 amp circuit with 14 gauge wire; 0.025 second GFCI Trip Time; The outlet is front facing, It has an easy to read diagnostic indicator; Built in protection against shock; Most used application for this product would be a bathroom vanity
Installation Notes	Standard 3-inch and 4-inch Keyhole Slots
Warranty	5-Years