SATCO NUVO

Project Name

ocation

Prepared By



NUVO 64-145

TAPE/RGBTW-HO/IP65/JBOX/SF/64'

Notes

vw1 10-27-2025 05:20

General	
Status	Active
Fixture Type	Tape Light
Finish	White
Wattage	68W
Lumen Output	6300L
CCT (Kelvin)	2700K
IP Rating	IP65
Indoor or Outdoor Fixture	Indoor; Outdoor
Smart Product Info	
IOT Enabled	Yes
Integrated Camera	No
Communication Protocol	WiFi-2.4GHz
Voice Assistants Supported	Alexa; Google Home; Siri; SmartThings
Software Supported	Tuya/Starfish APP
Specifications	
Technology	LED
Technology Color Temperature	RGB and Tunable White
Color Temperature	RGB and Tunable White
Color Temperature CRI	RGB and Tunable White 80+
Color Temperature CRI Voltage	RGB and Tunable White 80+ 24V
Color Temperature CRI Voltage Rated Hours	RGB and Tunable White 80+ 24V 50000
Color Temperature CRI Voltage Rated Hours Operating Temperature	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F)
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.)	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.) Material	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.) Material Dimensions	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94 Plastic
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.) Material Dimensions Width (in.)	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94 Plastic
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.) Material Dimensions Width (in.) Length (in.)	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94 Plastic
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.) Material Dimensions Width (in.) Length (in.) Compliance	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94 Plastic 0.55 787.44
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.) Material Dimensions Width (in.) Length (in.) Compliance Safety Listing	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94 Plastic 0.55 787.44 CETLus - Listed
Color Temperature CRI Voltage Rated Hours Operating Temperature Dimmable Dimming Note Weight (lb.) Material Dimensions Width (in.) Length (in.) Compliance Safety Listing Location Rating	RGB and Tunable White 80+ 24V 50000 -20C (-4F) to +40C (+104F) Yes-Dimmable Only with Starfish App or Remote Control 7.94 Plastic 0.55 787.44 CETLus - Listed Wet

Safety Listing	cETLus - Listed
Location Rating	Wet
ENERGY STAR	No
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
Canadian Standard ICES-005	Class B
SDS Sheet	LED Fixture

Additional Information	
Additional Information	Driver Wattage is 80W; Driver Voltage is 120V- 277V
Specification Note	Linkable - No; Cuttable - Yes; The Outdoor Tape can be cut to size at the designated markings and maintain the IP65 rating & Warranty only if the 64-166 End Cap and Glue are used to reseal the tape. If the Outdoor Tape is cut and 64-166 End Cap and Glue are not used to reseal the tape, the IP Rating & Warranty becomes invalidated. High Brightness; Sync to Music
Installation Notes	2 reels of 32 feet (10M) to make 64 feet (20M) total; Mounting Clips for outdoor installation
Includes	Kit includes: Outdoor Rated Driver/Junction Box; Receiver; RF Remote; 80 Mounting Clips; 2-10M Reels
Warranty	1-Year

