SATCO NUVO

Project Name

Location Prepared By



Notes

w] 08-26-2025 22:3

Status		
Fixture Type Strip Light Finish White Wattage 38W Lumen Output 4860L CCT (Kelvin) 5000K IP Rating IP44 Indoor Outdoor Fixture Indoor Smart Product Info IOT Enabled No Integrated Camera No Specifications Technology LED LED Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lib.) 5.23 Dimensions Height (in.) 2.68 Width (in.)	General	
Finish White Wattage 38W Lumen Output 4860L CCT (Kelvin) 5000K IP Rating IP44 Indoor Outdoor Fixture Indoor Smart Product Info IOT Enabled No Integrated Camera No Specifications Technology LED Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2kV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 <tr< th=""><th>Status</th><th>Active</th></tr<>	Status	Active
Wattage 38W Lumen Output 4860L CCT (kelvin) 5000K IP Rating IP44 Indoor or Outdoor Fixture Indoor Smart Product Info IOT Enabled No Integrated Camera No Specifications Technology LED Color Temperature Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (Ib.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Co	Fixture Type	Strip Light
Lumen Output 4860L CCT (Kelvin) 5000K IP Rating IP44 Indoor Outdoor Fixture Indoor Smart Product Info IOT Enabled No Integrated Camera No Specifications Technology LED LED Color Temperature Natural Light CRI 80+ Voltage 120v-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus	Finish	White
CCT (Kelvin) 5000K IP Rating IP44 Indoor Or Outdoor Fixture Indoor Smart Product Info IOT Enabled No Integrated Camera No Specifications Technology LED Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified <td>Wattage</td> <td>38W</td>	Wattage	38W
IP Rating IP44 Indoor or Outdoor Fixture Indoor Smart Product Info IOT Enabled No Integrated Camera No Specifications Technology LED Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note -0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (Ib.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	Lumen Output	4860L
Indoor or Outdoor Fixture Smart Product Info IOT Enabled Integrated Camera No Specifications Technology LED Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle Rated Hours Souoo Operating Temperature Yes-Dimmable Ves-Dimmable Ves-Dimmable Ves-Dimming Note Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Weight (Ib.) Dimensions Height (in.) 2.68 Width (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved And California Status Lawful for sale California Status California Prop 65 Lead RoHS Compliant Yes	CCT (Kelvin)	5000K
IOT Enabled No Integrated Camera No Specifications Technology LED Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note O-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	IP Rating	IP44
IOT Enabled No Integrated Camera No Specifications Technology LED Color Temperature Natural Light CRI 80+ Voltage 120v-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale California Prop 65 Lead ROHS Compliant Visua Page Prop 12 Lep Ves	Indoor or Outdoor Fixture	Indoor
Integrated Camera Specifications Technology Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle Rated Hours Operating Temperature O-20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note O-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) Compliance Safety Listing CULus - Certified Location Rating Damp UL Application ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead ROHS Compliant	Smart Product Info	
Technology LED Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	IOT Enabled	No
Technology Color Temperature Natural Light CRI 80+ Voltage 120V-277V Beam Angle Rated Hours Operating Temperature Dimmable Dimming Note Lens Material Polycarbonate (PC) Surge Protection Max. Connectable Units Weight (lb.) Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) Ware Compliance Safety Listing UL Application ENERGY STAR No DLC Approved California Status Lawful for sale California Prop 65 Lead California Prop 65 Lead California Prop 65 Lead California Prop 65 Lead Compliante 110 Ratural Light 204-24 Status Leaful (in.) Ratural Light 207-24 Status Leaful (in.) Voltage Proved Ves Ves Value - Certified Location Rating Damp Leaful (in.) Leaful (in	Integrated Camera	No
Color Temperature CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note O-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lauful for sale California Prop 65 Lead ROHS Compliant	Specifications	
CRI 80+ Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing cULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROME SOUND SOUN	Technology	LED
Voltage 120V-277V Beam Angle 110 Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Yes-Dimmable Dimming Note 0-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 RoHS Compliant	Color Temperature	Natural Light
Beam Angle Rated Hours 50000 Operating Temperature -20C (-4F) to +40C (+104F) Dimmable Pimming Note Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing Location Rating UL Application ENERGY STAR No DLC Approved California Status Lawful for sale California Prop 65 Lead California Prop 65 RoHS Compliante -20C (-4F) to +40C (+104F) Yes Possion 2.08 Cultus - Certified Cultus - Certified Cultus - Certified California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes	CRI	80+
Rated Hours Operating Temperature Operating Temperature Dimmable Polycarbonate (PC) Surge Protection Max. Connectable Units Weight (Ib.) Dimensions Height (in.) Compliance Safety Listing Location Rating UL Application ENERGY STAR DLC Approved California Status California Status California Prop 65 Lead Polycarbonate (PC) Built-in tourge protection - 2KV Up to 10 units S.23 Dimensions Up to 10 units S.23 Culus - Certified Culus - Certified Ceiling / Wall ENERGY STAR No Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead ROHS Compliant Yes	Voltage	120V-277V
Operating Temperature Dimmable Dimmable Pes-Dimmable O-10V Dimming Only Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Weight (lb.) Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) Compliance Safety Listing Location Rating UL Application ENERGY STAR No DLC Approved California Status Lawful for sale California Prop 65 RoHS Compliant Yes	Beam Angle	110
Dimmable Yes-Dimmable Dimming Note Dimming Note Description Dimersions Height (in.) Compliance Safety Listing Location Rating UL Application ENERGY STAR DLC Approved California Status California Status California Prop 65 Rolls Weldy (PC) Built-in surge protection - 2KV Up to 10 units Up to 10 units S.23 Dimersions Length (in.) 2.68 Width (in.) 2.56 47.87 CULus - Certified Damp Ceiling / Wall ENERGY STAR No Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead Roll Scompliant Yes	Rated Hours	50000
Dimming Note Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (Ib.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing Cullus - Certified Location Rating Damp UL Application ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 Lead ROHS Compliant Polycarbonate (PC) Built-in surge protection - 2KV Up to 10 units Up to 10 units Up to 10 units Cell units Cullus - Certified Cullus - Certified Lawful for sale in California Lawful for sale Lawful for sale	Operating Temperature	-20C (-4F) to +40C (+104F)
Lens Material Polycarbonate (PC) Surge Protection Built-in surge protection - 2KV Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 ROHS Compliant Polycarbonate (PC) Built-in surge protection - 2KV Up to 10 units Up to 10 units Cell units Cell units Polycarbonate (PC) Built-in surge protection - 2KV Up to 10 units Cell units Length (in.) - 2.68 Up to 10 units Cullus - Certified Cullus - Certified Location Rating Damp Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant	Dimmable	Yes-Dimmable
Surge Protection Built-in surge protection - 2KV Max. Connectable Units Weight (Ib.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing Location Rating Damp UL Application ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status California Prop 65 RoHS Compliant Up to 10 units Leaf Ves	Dimming Note	0-10V Dimming Only
Max. Connectable Units Up to 10 units Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing cULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	Lens Material	Polycarbonate (PC)
Weight (lb.) 5.23 Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing cULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	Surge Protection	Built-in surge protection - 2KV
Dimensions Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing cULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	Max. Connectable Units	Up to 10 units
Height (in.) 2.68 Width (in.) 2.56 Length (in.) 47.87 Compliance Safety Listing CULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes	Weight (lb.)	5.23
Width (in.) Length (in.) 47.87 Compliance Safety Listing Location Rating Damp UL Application ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	Dimensions	
Length (in.) 47.87 Compliance Safety Listing	Height (in.)	2.68
Safety Listing cULus - Certified Location Rating Damp UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes		2.56
Safety Listing CULus - Certified Location Rating Damp UL Application ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	Length (in.)	47.87
Location Rating UL Application ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 ROHS Compliant Lead Yes	Compliance	
UL Application Ceiling / Wall ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead ROHS Compliant Yes	Safety Listing	cULus - Certified
ENERGY STAR No DLC Approved No California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes	Location Rating	Damp
DLC Approved California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes	UL Application	Ceiling / Wall
California Status Lawful for sale in California Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes	ENERGY STAR	No
Title 20 / 24 Status Lawful for sale California Prop 65 Lead RoHS Compliant Yes	DLC Approved	No
California Prop 65 Lead ROHS Compliant Yes	California Status	Lawful for sale in California
RoHS Compliant Yes	Title 20 / 24 Status	Lawful for sale
RoHS Compliant Yes	California Prop 65	Lead
FCC Compliant Yes	RoHS Compliant	
	FCC Compliant	Yes
Canadian Standard ICES-005 Class A	Canadian Standard ICES-005	Class A
SDS Sheet LED_Fixture	SDS Sheet	LED_Fixture

Additional information	
Warranty	5-Years

