SATCO" NUVO"

Project Name

Location

Prepared By



NUVO 65-225 LED VAPOR PROOF CEILING MOUNT

Notes

StatusDiscontinuedFixture TypeVapor ProofFinishSilverWattage20WLumen Output1800LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureOutdoorSpecifications5000CRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)5.66ComplianceVetSafety ListingCETLus - ListedLocation RatingWetUL ApprovedNoDLC ApprovedNoCA T20 / T24 RationaleI20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Frop 65LeadRoHS CompliantYesSDS SheetLED_Fixture	General	
FinishSilverWattage20WLumen Output1800LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureOutdoorSpecificationsSomeTechnologyLEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DinmableNon-DinmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)5.66ComplianceSafety ListingSafety ListingCETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Status	Discontinued
Wattage20WLumen Output1800LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureOutdoorSpecificationsTechnologyLEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)5.66ComplianceSafety ListingSafety ListingCETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCalifornia StatusLawful for saleCompliantYesFCC CompliantYes	Fixture Type	Vapor Proof
Lumen Output1800LLumen Output1800LCCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureOutdoorSpecificationsEEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions5.66ComplianceSafety ListingSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleI20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesCompliantYes		
CCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureOutdoorSpecificationsTechnologyTechnologyLEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)15.66ComplianceVetSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleI20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFC CompliantYes	Wattage	20W
CCT (Kelvin)4000KTemperatureCool WhiteIP RatingIP65Indoor or Outdoor FixtureOutdoorSpecificationsEDTechnologyLEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DinmableNon-DinmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions5.66ComplianceSafety ListingLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for sale in CaliforniaCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Lumen Output	1800L
IP RatingIP65Indoor or Outdoor FixtureOutdoorSpecificationsEEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)5.66ComplianceCETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes		4000K
Indoor or Outdoor FixtureOutdoorSpecificationsTechnologyLEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensionsJinensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	,	Cool White
SpecificationsTechnologyLEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)11.09Width (in.)5.66ComplianceVetSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	IP Rating	IP65
TechnologyLEDCRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)5.66ComplianceSafety ListingLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYes	Indoor or Outdoor Fixture	Outdoor
CRI80CRI80Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadRoHS CompliantYesFCC CompliantYes	Specifications	
Voltage100V-277VRated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)5.66ComplianceVetSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Technology	LED
Rated Hours50000Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	CRI	80
Operating Temperature-30C (-22F) to +50C (+122F)DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Voltage	100V-277V
DimmableNon-DimmableLens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYes	Rated Hours	50000
Lens MaterialGlassSurge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYes	Operating Temperature	-30C (-22F) to +50C (+122F)
Surge ProtectionBuilt-in surge protection - 2KVWeight (lb.)3.79MaterialDie-cast AluminumDimensions11.09Width (in.)5.66ComplianceETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Dimmable	Non-Dimmable
Weight (lb.)3.79MaterialDie-cast AluminumDimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures NotRegulatedLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYes	Lens Material	Glass
MaterialDie-cast AluminumDimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCompliantYesFCC CompliantYes	Surge Protection	Built-in surge protection - 2KV
DimensionsHeight (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Weight (lb.)	3.79
Height (in.)11.09Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLeadCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Material	Die-cast Aluminum
Width (in.)5.66ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Dimensions	
ComplianceSafety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Height (in.)	11.09
Safety ListingcETLus - ListedLocation RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Width (in.)	5.66
Location RatingWetUL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Compliance	
UL ApplicationCeiling / WallEnergy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Safety Listing	cETLus - Listed
Energy StarNoDLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadROHS CompliantYesFCC CompliantYes	Location Rating	Wet
DLC ApprovedNoCA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	UL Application	Ceiling / Wall
CA T20 / T24 RationaleT20 Exempt - Fixtures Not RegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	Energy Star	No
CA 120 / 124 RationaleRegulatedCalifornia StatusLawful for sale in CaliforniaTitle 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	DLC Approved	No
Title 20 / 24 StatusLawful for saleCalifornia Prop 65LeadRoHS CompliantYesFCC CompliantYes	CA T20 / T24 Rationale	•
California Prop 65LeadRoHS CompliantYesFCC CompliantYes	California Status	Lawful for sale in California
RoHS CompliantYesFCC CompliantYes	Title 20 / 24 Status	Lawful for sale
FCC Compliant Yes	California Prop 65	Lead
	RoHS Compliant	Yes
	FCC Compliant	Yes
		LED_Fixture

Warranty

5 Year Limited - Fixtures

